


NELSON COUNTY SCHOOLS - WEST CAMPUS


THOMAS NELSON HIGH SCHOOL - PHASE III (AUDITORIUM)




2885 NEW SHEPHERDSVILLE ROAD (HWY 245)
BARDSTOWN, KENTUCKY 40004



NELSON COUNTY
BOARD OF EDUCATION
BARDSTOWN, KENTUCKY



BG# 15-229



LIST OF DRAWINGS

GENERAL SITE AND CIVIL

- C1.0 SITE LAYOUT
- C2.0 SITE GRADING AND DETAILS

"HS" - HIGH SCHOOL BUILDING

- D1.0 ARCHITECTURAL DEMOLITION PLAN

- S0.1 GENERAL NOTES
- S0.2 SPECIAL INSPECTIONS AND SCHEDULES
- S0.3 TYPICAL DETAILS
- S0.4 TYPICAL DETAILS
- S1.1 FOUNDATION PLAN
- S2.1 UPPER FLOOR AND MEZZANINE FRAMING
- S3.1 ROOF FRAMING PLANS
- S4.1 SECTION AND DETAILS
- S5.1 SECTION AND DETAILS
- S5.2 SECTION AND DETAILS
- S5.3 SECTION AND DETAILS
- S6.1 SECTION AND DETAILS

- A0.1 LIFE SAFETY PLAN AND CODE DATA
- A1.0 FLOOR PLAN
- A1.1 MEZZANINE LEVEL FLOOR PLAN
- A1.2 ROOF AND CEILING PLANS
- A1.3 DRESSING AREA CEILING PLAN AND DETAILS
- A2.0 EXTERIOR ELEVATIONS
- A3.0 BUILDING SECTIONS
- A3.1 BUILDING SECTIONS
- A3.2 BUILDING SECTIONS
- A3.3 WALL SECTIONS
- A3.4 STAIR DETAILS
- A3.5 STAIR AND LADDER SECTIONS
- A4.0 INTERIOR ELEVATIONS
- A5.0 SCHEDULES AND FINISHES
- A5.1 FURNITURE PLAN
- A6.0 TYPICAL DETAILS
- A6.1 TYPICAL DOOR AND WINDOW DETAILS

- P1.1 FIRE PROTECTION PLANS
- P1.0 PLUMBING SCHEDULES AND DETAILS
- P1.1 FLOOR PLAN - PLUMBING

- M1.1 MECHANICAL LEGEND AND GENERAL NOTES
- M2.1 FLOOR PLAN - MECHANICAL
- M2.2 MEZZANINE - MECHANICAL
- M3.1 MECHANICAL SCHEDULES
- M4.1 MECHANICAL DETAILS
- M4.2 MECHANICAL MEZZANINE SECTIONS
- M5.1 MECHANICAL SCHEDULES

- E1.1 ELECTRICAL LEGEND
- E2.1 LEVEL 1 - LIGHTING
- E2.2 MEZZANINE - LIGHTING
- E3.1 LEVEL 1 - POWER / SYSTEMS
- E3.2 MEZZANINE LEVEL - POWER / SYSTEMS
- E4.1 ELECTRICAL INTERCONNECTION PLAN
- E5.1 ELECTRICAL SCHEDULES AND DETAILS
- E5.2 ELECTRICAL DETAILS
- E5.3 ELECTRICAL DETAILS
- E5.4 ELECTRICAL SCHEDULES AND DETAILS
- E6.1 ELECTRICAL DETAILS
- E7.1 ELECTRICAL SCHEDULES AND DETAILS


studio kremer architects

3258 Ruckriegel Parkway, Louisville, KY 40299





TEL 502.499.1100 FAX 499.1101

CONSTRUCTION DOCUMENTS


		studio kremer architects
Horizon ENGINEERING, LLC		
3258 Ruckriegel Parkway, Louisville, KY 40299 TEL 502.499.1100 FAX 499.1101 studio		
Civil Engineering & Land Surveying 111 North Second Street, P.O. Box 654 Bardstown, KY 40004 Phone (502) 348-4350 • Fax: (502) 348-4240		



CONSTRUCTION DOCUMENTS



NOTE:
THESE PLANS ARE TO ENCOMPASS PHASE 3 CONSTRUCTION ACTIVITIES, WHICH INCLUDES THE AUDITORIUM ADDITION TO THE SOUTH SIDE OF THE SCHOOL BUILDING, CONNECTING DOWNSPOUTS TO EXISTING STORM, NEW SIDEWALK WITH DETECTABLE PAVERS AROUND PERIMETER OF ADDITION, NEW ASPHALT PAVEMENT FOR STAGE LOADING AREA AND DRIVE, PEA GRAVEL BETWEEN BUILDING & SIDEWALK AND REPAIR TO ANY EXISTING FINISHED AREAS AROUND BUILDING ADDITION & NEW SIDEWALK. ANY LAWN AREAS THAT ARE DISTURBED DURING CONSTRUCTION NEED TO BE REPAVED AND ENSURE THAT VEGETATION IS RE-ESTABLISHED.



② KEY PLAN
1" = 80'-0"


CONSTRUCTION DOCUMENTS

DEMOLITION PLAN	NELSON COUNTY SCHOOLS - WEST CAMPUS		
THOMAS NELSON H.S.	288 WILDCAT LANE BARDSTOWN, KENTUCKY 40004		
PHASE III	DESIGNED TO EARN THE GREEN BIRD'S EYE	2885 NEW SHEPHERDSVILLE ROAD (HWY 245)	BARDSTOWN, KENTUCKY 40004
BG 15-229	DATE : 12/8/2015	DRAWN BY : BVD	CHECKED BY : SW
2011-02	REVISIONS :		
PHASE - 3			
D 1.0			
HS			

studio **kremer** architects

3258 Ruckriegel Parkway, Louisville, KY 40299

TEL 502.249.1100 FAX 459.1101



STRUCTURAL GENERAL NOTES

STRUCTURAL DESIGN CRITERIA

1. APPLICABLE BUILDING CODES:
 - A. 2013 KENTUCKY BUILDING CODE
 - B. 2012 INTERNATIONAL BUILDING CODE
 - C. ASCE STANDARD: ASCE 7-10

2. PROJECT LOCATION: BARDSTOWN, KENTUCKY (NELSON COUNTY)

3. DESIGN LOADS:

- A. FLOOR LIVE LOADS
 - 1. SLABS ON GRADE.....100 PSF
 - 2. STADIUM SEATING.....100 PSF
 - 3. MECHANICAL ROOMS.....80 PSF

B. ROOF LOAD20 PSF

- C. SNOW LOADS
 - 1. GROUND SNOW LOAD: Pg=15 PSF
 - 2. FLAT-ROOF SNOW LOAD: Pf=6.5 PSF
 - 3. SNOW EXPOSURE FACTOR: Ce=1.0
 - 4. THERMAL FACTOR: Ct=1.0
 - 5. SNOW LOAD IMPORTANCE FACTOR: Is = 1.1

D. WIND LOADS

1. BASIC WIND SPEED=120 MPH (ULTIMATE) (3-SECOND GUSTS)
2. WIND IMPORTANCE FACTOR: Iw=1.0
3. EXPOSURE CATEGORY: B
4. DESIGN WIND PRESSURE FOR COMPONENTS AND CLADDING: P=23.0 PSF (WORKING STRESS)
5. DESIGN WIND PRESSURE FOR MAIN WINDFORCE RESISTING SYSTEM: P=15.0 PSF (WORKING STRESS)
6. INTERNAL PRESSURE COEFFICIENT: ±0.18

E. EARTHQUAKE LOADS

1. BUILDING OCCUPANCY CATEGORY III EARTHQUAKE USE GROUP: III
2. MAPPED SPECTRAL RESPONSE ACCELERATION: Ss=0.229%, S1=0.117%
3. SEISMIC DESIGN CATEGORY B
4. SITE CLASS C
5. RESPONSE MODIFICATION FACTOR=4.0
6. SYSTEM OVER STRENGTH FACTOR=2.5
7. DEFLECTION AMPLIFICATION FACTOR=4.0
8. ANALYSIS PROCEDURE: EQUIVALENT LATERAL FORCE PROCEDURE
9. SPECTRAL RESPONSE COEFFICIENTS Sos=0.183, Sb1=0.133 Cs=0.0572
10. DESIGN BASE SHEAR =0.05/2 W
11. BASIC STRUCTURAL SYSTEM: ORDINARY REINFORCED CONCRETE SHEAR WALLS

CONCRETE

1. ALL CONCRETE FOR GENERAL USE (INCLUDING FOOTINGS, FOUNDATION WALLS AND ICF WALLS) SHALL HAVE A MINIMUM 28 DAY COMPRESSIVE STRENGTH OF 4000 PSI.
2. REINFORCING STEEL SHALL BE AS FOLLOWS:
 - STIRRUPS AND TIERS.....ASTM A615 GRADE 60
 - ALL OTHER REINFORCING.....ASTM A615 GRADE 60
 - *WELDED WIRE FABRIC FOR USE IN ELEVATED SLABS ON METAL DECK SHALL BE SUPPLIED IN FLAT SHEETS, NOT ROLLS. ROLLS OF WELDED WIRE FABRIC PROVIDED FOR THIS PURPOSE WILL BE REJECTED AND RETURNED TO SUPPLIER.

3. PROVIDE BAR SUPPORTS AND SPACERS IN ACCORDANCE WITH ACI DETAILING MANUAL. ALL BAR SUPPORTS IN AREAS WHERE CONCRETE WILL BE EXPOSED SHALL HAVE PLASTIC FEET. PRECAST CONCRETE (fc'=3000psi) BLOCKS 3"x5"x3" SHALL BE USED TO SUPPORT REINFORCING OFF THE GROUND. AT ALL OTHER LOCATIONS, CHAIRS OR STANDEES SHALL BE USED.

4. DETAILING, FABRICATION AND PLACING OF REINFORCING SHALL CONFORM TO APPLICABLE PROVISIONS OF ACI 315 AND ACI 318.

5. SLABS, FOUNDATION WALLS AND FOOTINGS SHALL HAVE NO HORIZONTAL JOINTS. ANY STOP IN CONCRETE WORK MUST BE MADE WITH VERTICAL KEYED BULKHEADS. ALL REINFORCEMENT SHALL CONTINUE THROUGH JOINTS.

6. BEFORE PLACING CONCRETE, THE CONTRACTOR SHALL NOTIFY ALL SUBCONTRACTORS TO BE SURE ALL SLEEVES, CONDUIT, CHASES, ETC. ARE PROPERLY INSTALLED. THE CONTRACTOR SHALL NOTIFY THE ARCHITECT/ENGINEER AS SOON AS PRACTICAL, BUT AT LEAST 24 HOURS PRIOR TO PLACING CONCRETE TO ALLOW FOR INSPECTION OF REINFORCING AND EMBEDDED ITEMS.

7. MATERIALS SHALL COMPLY WITH REQUIREMENTS OF DESIGNATED SPECIFICATIONS OF AMERICAN SOCIETY FOR TESTING AND MATERIALS, 1916 RACE STREET, PHILADELPHIA, PENNSYLVANIA.

8. CONSTRUCTION PROCEDURES SHALL COMPLY WITH RECOMMENDATIONS SET FORTH IN DESIGNATED STANDARDS OF AMERICAN CONCRETE INSTITUTE, P.O. BOX 9094, FARMINGTON HILLS, MICHIGAN 48333.

9. ADMIXTURE OTHER THAN AIR-ENTRAINING SHALL NOT BE USED WITHOUT APPROVAL OF THE ARCHITECT/ENGINEER. AIR-ENTRAINING ADMIXTURES TO CONFORM TO ASTM C260.

10. CURING COMPOUND SHALL CONFORM TO FEDERAL SPECIFICATION TT-C800A, AND A.S.T.M. C309. THE MATERIAL SHALL BE EQUAL TO SONNEBORN KUR-N-SEAL, MASTERSSEAL, BY MASTER BUILDERS, OR CLEAR SEAL, BY W.R. GRACE.

11. ALL REINFORCING SPLICES SHALL BE CLASS B TENSION LAP SPLICING.

12. SPREAD BARS AROUND SMALL OPENINGS AND SLEEVES IN SLABS AND WALLS WHERE POSSIBLE AND WHERE BAR SPACING WILL NOT EXCEED 1.5 TIMES THE NORMAL SPACING. DISCONTINUE BARS AT LARGE OPENINGS WHERE NECESSARY AND PROVIDE AN AREA OF REINFORCEMENT EQUAL TO THE INTERRUPTED REINFORCEMENT, DISTRIBUTING ONE-HALF OF THIS REINFORCEMENT EACH SIDE OF THE OPENING (CLASS B TENSION LAP SPLICED). HOLES LARGER THAN 12" IN ANY DIRECTION SHALL HAVE (1/2" x 5"-0") DIAGONAL BAR IN BOTH FACES AT EACH CORNER.

13. PIER REINFORCEMENT SHALL BE DOWELED TO THE FOOTING. PROVIDE DOWELS EQUAL IN SIZE, NUMBER AND GRADE TO THE PIER REINFORCEMENT UNLESS OTHERWISE INDICATED. DOWELS SHALL BE LAPPED WITH THE PIER REINFORCEMENT.

14. PIER REINFORCEMENT SHALL BE THE SAME SIZE, NUMBER AND GRADE AS THE COLUMN/PILASTER REINFORCING, UNLESS OTHERWISE NOTED.

15. ALL VERTICAL CONCRETE SURFACES SHALL BE FORMED. HOWEVER, VERTICAL SURFACES OF FOOTINGS MAY BE EARTH-FORMED IF THE SOIL IS SUFFICIENTLY STIFF TO PREVENT CAVE-INS.

16. REINFORCING BARS SHALL BE IN PLACE AND SECURED PRIOR TO POURING CONCRETE.

17. REINFORCING BAR SHOP DRAWINGS SHALL SHOW NUMBER, SIZE AND LOCATION OF BARS, AS WELL AS LAP LENGTH AND CLEAR COVER.

18. ALL CONCRETE SLABS SUPPORTED BY SOIL OR GRANULAR SUB-BASE SHALL CONTAIN CONTROL JOINTS AND CONSTRUCTION JOINTS, AT SPACING NOT TO EXCEED 20 FEET ON CENTER IN BOTH DIRECTIONS. SAW-CUT JOINTS SHALL BE INSTALLED AS SOON AS THE CONCRETE IS HARD ENOUGH TO WITHSTAND SAWING WITHOUT RAVELING JOINT EDGES OR DISLOCATING COARSE AGGREGATE PARTICLES. LIGHTWEIGHT EARLY-CUT SAWS SHALL BE USED. CONTRACTOR SHALL SUBMIT CONSTRUCTION AND CONTROL JOINT LAYOUT FOR APPROVAL PRIOR TO PLACING CONCRETE SLABS.

19. DOVETAIL SLOTS SHALL BE INSTALLED IN ALL CONCRETE WORK WHICH IS TO RECEIVE BRICK VENEER OR OTHER FACING MATERIALS.

FOUNDATIONS

1. ASSUMED ALLOWABLE SOIL BEARING PRESSURE:
 - ISOLATED FOOTINGS.....2,500 PSF
 - CONTINUOUS FOOTINGS.....2,500 PSF
2. FOUNDATIONS HAVE BEEN SIZED IN ACCORDANCE WITH THE RECOMMENDATIONS OF THE GEOTECHNICAL EXPLORATION REPORT (SOILS REPORT) PREPARED BY GREENBAUM ASSOCIATES, INC., DATED MARCH 9, 2009 (GREENBAUM PROJECT NO. 09-021).
3. THE CONTRACTOR SHALL THOROUGHLY FAMILIARIZE HIMSELF WITH THE EARTHWORK SPECIFICATIONS AND SHALL PERFORM ALL EARTHWORK OPERATIONS AND FOUNDATION INSTALLATION OPERATIONS IN ACCORDANCE WITH THESE SPECIFICATIONS.
4. PRIOR TO CONSTRUCTION OF ANY PERMANENT STRUCTURE, ALL EXISTING SURFACE FILL, ALL TOPSOIL AND ORGANIC MATERIAL, ALL WET, SOFT, LOOSE, OR UNDESIRABLE SOIL, AND ALL OLD ABANDONED CONCRETE SHALL BE REMOVED TO THE EXTENT REQUIRED BY THE EARTHWORK SPECIFICATIONS.
5. CONCRETE FOR FOOTINGS SHALL BE PLACED THE SAME DAY EXCAVATIONS ARE OPENED. IF THIS IS IMPOSSIBLE, STEPS SHALL BE TAKEN TO ADEQUATELY PROTECT THE OPEN EXCAVATION.
6. FOOTINGS AND SLABS ON GRADE SHALL BEAR ON FIRM NATURAL SOIL, OR ON PROPERLY COMPACTED ENGINEERED FILL, AS REQUIRED BY THE EARTHWORK SPECIFICATIONS. SOIL BEHIND FOOTINGS SHALL BE PROBED FOR ROCK TO VERIFY THAT THERE IS A MINIMUM SOIL DEPTH OF 6" BEHIND THE FOOTINGS. IF ROCK IS ENCOUNTERED, UNDERCUT & BACKFILL WITH CLAYEY SOIL PER TYPICAL DETAIL & SPECIFICATIONS.
7. ENGINEERED FILL & BACKFILL SHALL BE PLACED AND COMPACTED ACCORDING TO THE REQUIREMENTS OF THE SPECIFICATIONS.
8. THE OWNER WILL RETAIN A QUALIFIED GEOTECHNICAL ENGINEER TO INSPECT ALL BEARING SURFACES AND EARTHWORK OPERATIONS.
9. ALL FOOTING EXCAVATIONS SHALL BE INSPECTED BY A GEOTECHNICAL ENGINEER BEFORE CONCRETE IS PLACED. THE ADEQUACY OF THE BEARING STRATUM SHALL BE DETERMINED BY THE GEOTECHNICAL ENGINEER. ALL GEOTECHNICAL FIELD REPORTS SHALL BE SUBMITTED TO THE ARCHITECT/ENGINEER.

REINFORCED MASONRY

1. COMPRESSIVE STRENGTH OF CONCRETE MASONRY SHALL BE F'w=1500 PSI.
2. GROUT FOR BOND BEAMS AND GROUTED CELLS IN CONCRETE MASONRY UNITS SHALL BE PEA GRAVEL CONCRETE WITH A 28 DAY COMPRESSIVE STRENGTH OF 2500 PSI.
3. MORTAR FOR CONCRETE MASONRY SHALL BE TYPE S.
4. PROVIDE CONTINUOUS HORIZONTAL JOINT REINFORCING IN ALL REINFORCED MASONRY WALLS AT 16" O.C. UNLESS NOTED OTHERWISE.
5. SPLICES IN VERTICAL REINFORCEMENT SHALL BE LAPPED IN ACCORDANCE WITH THE LAP SPLICE TABLE.
6. ALL MASONRY WALLS SHALL BE LATERALLY BRACED BY THE CONTRACTOR UNTIL ALL STRUCTURAL FRAMING AND DECKING HAVE BEEN INSTALLED IN UNITS OF CONSTRUCTION ADJACENT TO THE WALLS.
7. A BOND BEAM WITH (2) #5 BARS SHALL BE PROVIDED AT THE TOP OF ALL WALLS, AND AT THE BEARING ELEVATION OF STEEL JOISTS, UNLESS NOTED OTHERWISE.
8. ALL CMU UNITS LOCATED BELOW GRADE SHALL BE GROUTED SOLID.
9. AT BEAMS, COLUMNS AND LINTELS BEARING ON MASONRY WALLS, UNLESS DETAILED OR NOTED OTHERWISE, FILL TWO BLOCK CORES SOLID WITH GROUT AND REINFORCE EACH CORE WITH ONE #5 VERTICAL REBAR FULL HEIGHT OF WALL.
10. UNLESS OTHERWISE SHOWN OR NOTED, PROVIDE A 7-1/2"x7-1/2"x3/8" BEARING PLATE WITH (2) 1/4" DIAMETER x 4" LONG HEADED STUDS EMBEDDED INTO GROUTED CORES AT ALL BEAMS BEARING ON MASONRY WALLS.
11. UNLESS OTHERWISE SHOWN OR NOTED, PLACE (1) #5 FULL-HEIGHT VERTICAL REINFORCING BAR AT ALL WALL CORNERS, ENDS OF WALLS, EACH SIDE OF CONTROL JOINTS, SIDES OF OPENINGS, AND WALL INTERSECTIONS. (PLACE (2) #5 BARS AT SIDES OF OPENINGS 10 FEET WIDE AND GREATER)
12. LOCATE VERTICAL CONTROL JOINTS IN ALL REINFORCED MASONRY WALLS AT A MAXIMUM SPACING OF 16"-0" O.C. LOCATIONS OF JOINTS SHALL BE APPROVED BY THE ARCHITECT PRIOR TO INSTALLATION. BOND BEAM AND REINFORCING SHALL BE CONTINUOUS THROUGH THE CONTROL JOINT.
13. SECURE ALL VERTICAL REINFORCING STEEL IN CMU WALLS WITH DUR-O-WALL REBAR POSITIONER OR APPROVED EQUAL.
14. GROUT FILL BEAM AND JOIST POCKETS IN CMU WALLS AFTER WELDS ARE INSPECTED.
15. CONTRACTOR SHALL SUBMIT DRAWINGS COORDINATED WITH THE MASONRY AND MEP CONTRACTORS, SHOWING THE MEP PENETRATIONS THROUGH LOAD BEARING WALLS. THESE DRAWINGS SHALL SHOW THE SIZE AND LOCATION OF ALL PENETRATIONS AND SHALL BE SUBMITTED TO THE ARCHITECT/ENGINEER FOR REVIEW PRIOR TO INSTALLATION

METAL FLOOR DECK

1. METAL FLOOR FORM DECKING SHALL BE FLAT ROLLED, GALVANIZED SHEETS OF STRUCTURAL QUALITY, MEETING THE REQUIREMENTS OF ASTM A653-94, GRADE 80. DECKING SHALL BE FACTORY GALVANIZED, COMPLYING WITH ASTM A653-94, COATING CLASS G90. CORROSION (PITCH x DEPTH) SHALL BE 2 1/2"x9 1/16" (MINIMUM) WITH GAUGE SUFFICIENT TO PROVIDE A MINIMUM SECTION MODULUS OF 0.039 IN.3. 26 GAUGE SHALL BE THE MINIMUM ALLOWED. DECKING SHALL BE FASTENED TO STEEL SUPPORTING MEMBERS WITH NO. 12 SELF-TAPPING METAL SCREWS AT 12" O.C., MAXIMUM SPACING. SIDE LAPS SHALL BE FASTENED TOGETHER WITH #10 SELF-TAPPING METAL SCREWS AT 12" O.C.
2. COMPOSITE METAL FLOOR DECKING SHALL BE FLAT ROLLED, GALVANIZED SHEETS OF STRUCTURAL QUALITY, MEETING THE REQUIREMENTS OF ASTM A653-94, STRUCTURAL GRADE. DECKING SHALL BE FACTORY GALVANIZED, COMPLYING WITH ASTM A653-94, COATING CLASS G90. THE DECK SHALL 1 1/2"x20 GAUGE TYPE 1.5VL120 AS MANUFACTURED BY VULCRAFT OR APPROVED EQUAL. DECKING SHALL BE FASTENED TO STEEL SUPPORTING MEMBERS WITH 5/8" DIAMETER Puddle WELD AT 12" O.C., MAXIMUM SPACING. SIDE LAPS SHALL BE WELDED AT 24" O.C. SHEAR STUDS MAY TAKE THE PLACE OF Puddle WELD.
3. ATTENTION IS CALLED TO THE FACT THAT THE METAL FLOOR DECK IS TO BE USED AS A PERMANENT FORM FOR THE CONCRETE FLOOR.
4. A TESTING COMPANY WILL BE RETAINED BY THE OWNER TO ENSURE THAT THE DECK IS FASTENED PROPERLY PRIOR TO PLACEMENT OF COVER MATERIALS. WRITTEN APPROVAL OF DECK INSTALLATION MUST BE SUBMITTED TO THE ARCHITECT/ENGINEER PRIOR TO PROCEEDING WITH CONSTRUCTION.
5. ACCESSORIES SHALL BE STANDARD WITH THE MANUFACTURER AND SHALL BE FURNISHED AS NECESSARY TO COMPLETE THE FLOOR DECK INSTALLATION. ACCESSORIES SHALL INCLUDE EDGE CLOSURE PLATES FOR ALL OPEN EDGES OF DECK.

METAL ROOF DECK

1. 1 1/2" ROOF DECK SHALL BE 20 GAUGE GALVANIZED (G90) WITH A FABRICATED DEPTH OF 1 1/2" AND A VALLEY SPACING OF 6". DECKING SHALL BE FACTORY GALVANIZED. DECKING SHALL CONFORM TO ASTM A653-94 STRUCTURAL QUALITY GRADE 33 OR HIGHER. DECKING SHALL BE FASTENED TO STEEL SUPPORTING MEMBERS AT 12" O.C., MAXIMUM SPACING, WITH NO. 12 SELF-TAPPING METAL SCREW. SIDE LAPS OF ADJACENT UNITS SHALL BE FASTENED WITH NO. 10 METAL SCREWS, AT 12" O.C., MAXIMUM SPACING. SHEETS SHALL BE CONTINUOUS FOR AT LEAST THREE SPANS WHERE POSSIBLE.
2. COMPLY WITH THE PROVISIONS OF THE LATEST EDITIONS OF THE FOLLOWING CODES, SPECIFICATIONS AND STANDARDS, EXCEPT AS OTHERWISE SHOWN OR SPECIFIED.
 - A. A.I.S.I. "SPECIFICATIONS FOR THE DESIGN OF COLD-FORMED STEEL STRUCTURAL MEMBERS".
 - B. AWS "STRUCTURAL WELDING CODE".
 - C. SDI "STEEL DECK DESIGN MANUAL".
3. ACCESSORIES SHALL BE STANDARD WITH THE MANUFACTURER AND SHALL BE FURNISHED AS NECESSARY TO COMPLETE THE ROOF DECK INSTALLATION.
4. PROVIDE MANUFACTURER'S STANDARD 14 GA. GALVANIZED SUMP PANS FOR EACH ROOF DRAIN. COORDINATE TYPE AND LOCATIONS WITH ARCHITECTURAL AND MECHANICAL DRAWINGS AND SPECIFICATIONS.
5. ATTENTION IS CALLED TO THE FACT THAT THE METAL ROOF DECK IS DESIGNED FOR DIAPHRAGM ACTION. THEREFORE, ADDED CARE MUST BE TAKEN TO ASSURE PROPER INSTALLATION PROCEDURES ARE FOLLOWED.
6. A TESTING COMPANY WILL BE RETAINED BY THE OWNER TO ENSURE THAT THE DECK IS FASTENED PROPERLY PRIOR TO PLACEMENT OF COVER MATERIALS. WRITTEN APPROVAL OF DECK INSTALLATION MUST BE SUBMITTED TO THE ARCHITECT/ENGINEER PRIOR TO PROCEEDING WITH CONSTRUCTION.
7. THE ENDS OF BRIDGING LINES TERMINATING AT MASONRY WALLS SHALL BE ANCHORED BY STRAP ANCHORS ATTACHED TO THE WALL UNLESS OTHERWISE SHOWN OR NOTED. GROUT JOIST POCKETS SHALL BE PROVIDED AS REQUIRED.
8. FURNISH AND INSTALL BOTTOM AND TOP CHORD LATERAL BRACING AS REQUIRED FOR STRENGTH AND STABILITY OF JOISTS.
9. ENDS OF STEEL JOISTS SHALL BE ANCHORED TO THE STEEL SUPPORTS BY WELDING.
10. EXTEND BOTTOM CHORD OF ALL JOISTS ON COLUMN LINES. WELD TO COLUMN AFTER ALL ROOF/FLOOR DEAD LOADS HAVE BEEN APPLIED.
11. PROVIDE ADDITIONAL L2x2x3/16 DIAGONALS AND FIELD WELD AT ALL POINTS WHERE EQUIPMENT IS SUPPORTED OR HUNG FROM THE CHORDS OF THE JOISTS. THE ANGLE SHALL EXTEND FROM THE POINT OF LOAD APPLICATION TO THE CLOSEST PANEL POINT IN THE OPPOSITE CHORD MEMBER. SEE TYPICAL DETAIL.
12. PROVIDE MISC. ANGLE FRAMING BETWEEN JOISTS AS REQUIRED AT ALL ROOF DRAINS AND MISC. FLOOR AND ROOF PENETRATIONS. SEE TYPICAL DETAIL.
13. PRIOR TO FABRICATION, SHOP DRAWINGS SHALL BE CHECKED BY THE CONTRACTOR AND SUBMITTED TO THE ENGINEER FOR REVIEW. SHOP DRAWINGS SHALL INCLUDE JOIST LAYOUT, ERECTION DETAILS, CONNECTION DETAILS, BRIDGING DETAILS, MARK, TYPE AND LOCATION.
14. ALL STEEL JOISTS SHALL BE PRODUCED BY AN S.J.I. MEMBER OR, IF PRODUCER IS NOT AN S.J.I. MEMBER, SHOP DRAWINGS SHALL BEAR THE SEAL AND SIGNATURE OF AN ENGINEER REGISTERED IN THE STATE WHERE THE JOISTS WILL BE ERECTED, WHO SHALL CERTIFY THAT THE JOISTS ARE DESIGNED AND FABRICATED IN ACCORDANCE WITH THE A.I.S.C. AND S.J.I. SPECIFICATIONS.
15. DESIGN JOIST TOP CHORD EXTENSIONS AND EXTENDED ENDS FOR DEAD LOADS AND LIVE LOADS OF BACK SPAN.
16. MISCELLANEOUS

 1. SHRINKAGE-RESISTING GROUT FOR USE BEHIND COLUMN BASE PLATES AND BEAM BEARINGS SHALL BE PRE-MIXED, FACTORY PACKAGED, NON-STAINING, NON-METALLIC, NON-GASING MORTAR GROUTING COMPOUND, COMPLYING WITH THE REQUIREMENTS OF A.S.T.M. C1107. GROUT SHALL HAVE A MINIMUM 28 DAY COMPRESSIVE STRENGTH OF 6,000 PSI.
 2. MATERIAL FOR USE AS VAPOR BARRIER BEHIND CONCRETE SLABS ON GRADE SHALL BE 10 MIL POLYETHYLENE SHEETS, BLACK IN COLOR, COMPLYING WITH ASTM D-2103. SHEETS SHALL BE LAPPED A MINIMUM OF 6" AT ALL EDGES. SPECIAL CARE SHALL BE TAKEN TO PREVENT PUNCTURING SHEETS PRIOR TO PLACEMENT OF SLABS.
 3. NO CHANGE IN SIZE OF STRUCTURAL ELEMENTS OR MODIFICATION THEREOF SHALL BE MADE, NOR ARE ANY OPENINGS OR SLEEVES THROUGH ANY STRUCTURAL ELEMENTS PERMITTED, UNLESS DETAILED ON THE DRAWINGS.
 4. CONSULT ARCHITECTURAL, MECHANICAL AND ELECTRICAL DRAWINGS FOR LOCATION, SIZES AND EXTENT OF CHASES, INSERTS, RECESSES, REGLETS, FINISHES, DEPRESSIONS, ETC. NOT SHOWN ON THE STRUCTURAL DRAWINGS.
 5. SPECIAL STRUCTURAL INSPECTIONS ARE REQUIRED ON THIS PROJECT IN ACCORDANCE WITH THE KENTUCKY BUILDING CODE. THE OWNER WILL BEAR THE COSTS OF THE SPECIAL STRUCTURAL INSPECTIONS. THE CONTRACTOR SHALL COORDINATE HIS WORK AND SCHEDULING, AND SHALL COOPERATE FULLY WITH THE AGENCIES PERFORMING THE SPECIAL STRUCTURAL INSPECTIONS.
 6. ALL WELDED WIRE FABRIC IN SLABS ON GRADE AND ELEVATED SLABS SHALL BE SUPPORTED BY CHAIRS, BOLSTERS, OR OTHER APPROVED SUPPORTING DEVICES. "PULLING-UP" OF MESH AFTER CONCRETE HAS BEEN PLACED IS NOT ACCEPTABLE.

17. CONTRACTOR RESPONSIBILITIES
 1. MATERIAL, WORKMANSHIP, AND DESIGN SHALL CONFORM TO THE REFERENCED BUILDING CODE.
 2. COORDINATE STRUCTURAL DOCUMENTS WITH THE ARCHITECTURAL, MECHANICAL, AND ELECTRICAL DOCUMENTS. ARCHITECT/STRUCTURAL ENGINEER SHALL BE NOTIFIED OF ANY DISCREPANCY OR OMISSION.
 3. VERIFY THE DIMENSIONS, ELEVATIONS AND SITE CONDITIONS BEFORE STARTING WORK. ANY DISCREPANCY BETWEEN SUCH DETAILS AND DIMENSIONS AS MAY OCCUR SHALL BE REPORTED TO THE ARCHITECT/ ENGINEER FOR CLARIFICATION BEFORE PROCEEDING WITH THE WORK.
 4. NOTIFY, IN WRITING, THE STRUCTURAL ENGINEER OF CONDITIONS ENCOUNTERED IN THE FIELD CONTRADICTORY TO THOSE SHOWN IN THE STRUCTURAL DOCUMENTS.
 5. CONTRACTOR HAS SOLE RESPONSIBILITY FOR MEANS, METHODS, TECHNIQUES, SEQUENCES, AND PROCEDURES OF CONSTRUCTION.
 6. CONTRACTOR HAS SOLE RESPONSIBILITY FOR THE DESIGN, ADEQUACY, AND SAFETY OF ERECTION BRACING, SHORING, TEMPORARY SUPPORTS, ETC.
 7. CONTRACTOR HAS SOLE RESPONSIBILITY TO COMPLY WITH ALL OSHA SAFETY REGULATIONS.
 8. SUBMITTALS
 - FURNISH TWO PRINTS OF SHOP DRAWINGS. FURNISH THREE COPIES OF OTHER STRUCTURAL SUBMITTALS.
 - REVIEW OF SUBMITTALS OR SHOP DRAWINGS BY THE STRUCTURAL ENGINEER DOES NOT RELIEVE THE CONTRACTOR OF THE SOLE RESPONSIBILITY TO REVIEW AND CHECK ALL SUBMITTALS AND SHOP DRAWINGS BEFORE SUBMITTING TO THE STRUCTURAL ENGINEER. CONTRACTOR REMAINS SOLELY RESPONSIBLE FOR ERRORS AND OMISSIONS ASSOCIATED WITH THE PREPARATION OF SHOP DRAWINGS AS THEY PERTAIN TO MEMBER SIZES, DETAILS, AND DIMENSIONS SPECIFIED IN THE CONTRACT DOCUMENTS.
18. GENERAL NOTES

GENERAL NOTES - WEST CAMPUS

THOMAS NELSON H.S. PHASE III

GENERAL NOTES - NEW SIEPHEROSVILLE ROAD (Hwy 245) BARDSTOWN, KENTUCKY 40004

BG 15-229 DATE: 12/08/2015 DRAWN BY: JEK CHECKED BY: TEL REVISIONS: 2011-02 PHASE - 3 SO.1 HS

SLESSER ENGINEERING, INC.
STRUCTURAL ENGINEERS
2325 LIME KILN LANE
LOUISVILLE, KENTUCKY 40229

studio kramer architects
3258 Ruckriegel Parkway, Louisville, KY 40299
TEL 502.499.1100 FAX 499.1101
CARL J. SLESSER
11/08/

SPECIAL STRUCTURAL INSPECTIONS

- THE OWNER SHALL EMPLOY ONE OR MORE SPECIAL INSPECTORS TO PROVIDE SPECIAL STRUCTURAL INSPECTIONS DURING CONSTRUCTION, IN ACCORDANCE WITH SECTION 1704 OF THE 2013 KENTUCKY BUILDING CODE AND THE 2012 INTERNATIONAL BUILDING CODE.
- MATERIALS AND WORK REQUIRING SPECIAL INSPECTIONS ARE AS FOLLOWS:
 - CONCRETE (INCLUDING ICF CONCRETE)
 - THE MATERIALS, SIZE, LOCATION AND INSTALLATION DETAILS OF REINFORCING STEEL SHALL BE INSPECTED FOR COMPLIANCE WITH THE APPROVED CONSTRUCTION DOCUMENTS AND ACI 318.
 - CONCRETE PLACING METHODS AND CURING OPERATIONS SHALL BE OBSERVED BY THE SPECIAL INSPECTOR FOR COMPLIANCE WITH THE APPROVED CONSTRUCTION DOCUMENTS, ACI 318 AND ACI 301.
 - FORMS FOR CONCRETE SHALL BE INSPECTED FOR COMPLIANCE WITH THE APPROVED CONSTRUCTION DOCUMENTS AND ACI 318.
 - VERIFY USE OF THE REQUIRED DESIGN MIX.
 - SAMPLE FRESH CONCRETE TO FABRICATE SPECIMENS FOR STRENGTH TESTS, TO PERFORM SLUMP AND AIR CONTENT TESTS, AND TO DETERMINE THE TEMPERATURE OF THE CONCRETE. VERIFY COMPLIANCE WITH THE APPROVED CONSTRUCTION DOCUMENTS AND ACI 318.
 - COMPLY WITH THE REQUIREMENTS OF TABLE 1, THIS SHEET.
 - STRUCTURAL STEEL
 - VERIFY THAT THE STEEL FABRICATOR MAINTAINS AND PROPERLY IMPLEMENTS DETAILED FABRICATION AND QUALITY CONTROL PROCEDURES.
 - SEPARATE INSPECTION OF FABRICATED STRUCTURAL STEEL AND THE FABRICATION PROCESS SHALL BE PERFORMED ON THE PREMISES OF THE FABRICATOR'S SHOP. IN-PLANT INSPECTIONS ARE NOT REQUIRED IF THE FABRICATOR IS CERTIFIED BY THE AISC.
 - BOLTS, NUTS AND WASHERS SHALL BE INSPECTED TO CONFIRM IDENTIFICATION MARKINGS AND CONFORMANCE TO ASTM STANDARDS SPECIFIED BY THE DESIGN ENGINEER. MANUFACTURER'S CERTIFICATE OF COMPLIANCE IS REQUIRED.
 - STRUCTURAL STEEL MEMBERS SHALL BE INSPECTED TO CONFIRM MATERIAL IDENTIFICATION MARKINGS AND CONFORMANCE TO ASTM STANDARDS SPECIFIED IN THE CONTRACT DOCUMENTS. PROVIDE MILITARY CERTIFICATION TEST REPORTS.
 - WELD FILLER MATERIALS SHALL BE INSPECTED TO CONFIRM CONFORMANCE TO AWS D1.1. MANUFACTURER'S CERTIFICATE OF COMPLIANCE IS REQUIRED.
 - EACH COMPLETE PENETRATION GROOVE WELD (SHOP WELD OR FIELD WELD) SHALL BE TESTED FOR THE FULL LENGTH OF THE WELD BY ULTRASONIC TESTING.
 - EACH FILLET WELD SHALL BE VISUALLY INSPECTED.
 - EACH HIGH STRENGTH BOLT SHALL BE INSPECTED TO CONFIRM THAT THE SPECIFIED TENSION OR SNUGNESS HAS BEEN ACHIEVED.
 - THE SPECIAL INSPECTOR SHALL PERFORM AN INSPECTION OF THE STEEL FRAME TO VERIFY COMPLIANCE WITH THE DETAILS SHOWN ON THE CONTRACT DOCUMENTS, SUCH AS BRACING, STIFFENING, MEMBER LOCATIONS AND PROPER APPLICATION OF JOINT DETAILS AT EACH CONNECTION.
 - VERIFY THAT ATTACHMENT OF ROOF DECK AND FLOOR DECK CONFORMS TO THE CONTRACT DOCUMENTS.
 - WELDS OF HEADED SHEAR STUDS TO STEEL BEAMS SHALL BE FIELD-TESTED FOR ADEQUACY.
 - COMPLY WITH THE REQUIREMENTS OF TABLE 2, THIS SHEET.
 - SOILS
 - DETERMINE THAT THE SITE HAS BEEN PREPARED IN ACCORDANCE WITH THE SOILS REPORT.
 - FILL PLACEMENT SHALL BE OBSERVED. VERIFY THAT IN-PLACE DENSITY, PROPER MATERIALS AND LIFT THICKNESS ARE IN ACCORDANCE WITH THE SOILS REPORT.
 - FOR SPREAD FOOTINGS BEARING ON SOIL, DETERMINE THAT THE SOIL IS SATISFACTORY TO SUPPORT THE DESIGN PRESSURES INDICATED IN THE SOILS REPORT AND ON THE DRAWINGS.
 - COMPLY WITH REQUIREMENTS OF TABLE 4, THIS SHEET.
 - REINFORCED CONCRETE MASONRY
 - VERIFY PROPORTIONS OF SITE-PREPARED MORTAR AND GROUT.
 - VERIFY CONSTRUCTION OF MORTAR JOINTS.
 - VERIFY THAT THE SIZE, GRADE AND TYPE OF CONCRETE MASONRY UNITS COMPLY WITH THE PROVISIONS OF THE CONSTRUCTION DOCUMENTS.
 - VERIFY LOCATIONS, REINFORCEMENT AND CONNECTORS, AND CLEANLINESS OF GROUT SPACE. VERIFY SIZE, GRADE AND TYPE OF REINFORCEMENT.
 - VERIFY TYPE, SIZE AND LOCATIONS OF ANCHORS AND EMBEDDED PLATES, INCLUDING CONNECTION DETAILS TO OTHER STRUCTURAL MEMBERS.
 - VERIFY ADEQUATE PROTECTION OF MASONRY DURING COLD AND/OR HOT WEATHER.
 - VERIFY PLACEMENT OF GROUT TO ENSURE COMPLIANCE WITH CONSTRUCTION DOCUMENTS.
 - PREPARE, OR OBSERVE THE PREPARATION OF, ALL REQUIRED MORTAR AND GROUT SPECIMENS FOR TESTING.
 - VERIFY THAT VERTICAL CONTROL JOINTS ARE PROPERLY INSTALLED AND CORRECTLY LOCATED.
 - COMPLY WITH THE REQUIREMENTS OF TABLE 3, THIS SHEET.
 - STEEL JOISTS
 - VERIFY SIZE, LOCATIONS AND SPACINGS OF STEEL BAR JOISTS.
 - VERIFY THAT BEARING AND CONNECTION DETAILS ARE IN ACCORDANCE WITH THE APPROVED SHOP DRAWINGS AND CONTRACT DOCUMENTS.
 - METAL ROOF DECK
 - VERIFY THAT PROPER DECK IS USED.
 - VERIFY THAT CONNECTIONS OF THE METAL DECK TO THE STRUCTURAL MEMBERS ARE IN ACCORDANCE WITH THE DESIGN DRAWINGS AND THE APPROVED SHOP DRAWINGS.
 - METAL FLOOR DECK
 - VERIFY THAT PROPER DECK IS USED.
 - VERIFY THAT CONNECTIONS OF THE METAL DECK TO THE STRUCTURAL MEMBERS ARE IN ACCORDANCE WITH THE DESIGN DRAWINGS AND THE APPROVED SHOP DRAWINGS.
 - CERTIFICATES OF COMPLIANCE (INSPECTION REPORTS) SHALL BE SUBMITTED WEEKLY BY THE SPECIAL INSPECTOR TO THE ENGINEER OF RECORD. REPORTS SHALL INDICATE THAT WORK INSPECTED WAS DONE IN CONFORMANCE WITH THE DRAWINGS. DISCREPANCIES SHALL BE BROUGHT TO THE IMMEDIATE ATTENTION OF THE CONTRACTOR FOR CORRECTION. IF DISCREPANCIES ARE NOT CORRECTED, THEY SHALL BE BROUGHT TO THE ATTENTION OF THE BUILDING OFFICIAL AND TO THE ENGINEER OF RECORD PRIOR TO COMPLETION OF THAT PHASE OF THE WORK.
 - AT THE COMPLETION OF THE TESTING AND SPECIAL INSPECTIONS, THE LICENSED PROFESSIONAL ENGINEER IN CHARGE OF PERFORMING THE SPECIAL INSPECTIONS SHALL SUBMIT TO THE ENGINEER OF RECORD A FINAL REPORT OF SPECIAL INSPECTIONS, AFFIXED WITH HIS/HER SEAL, DOCUMENTING COMPLETION OF ALL REQUIRED SPECIAL INSPECTIONS AND CORRECTION OF ANY DISCREPANCIES NOTED IN THE INSPECTIONS.
 - ADMINISTRATIVE AND PROCEDURAL REQUIREMENTS FOR SPECIAL STRUCTURAL INSPECTIONS AND TESTS ARE INDICATED IN SPECIFICATION SECTION 01411.

INSPECTION TASK	TABLE 1 REQUIRED VERIFICATION & INSPECTION OF CONCRETE CONSTRUCTION			
	FREQUENCY*		REFERENCE FOR CRITERIA	
	Continuous	Periodic	REFERENCED STANDARD	IBC
1. Inspection of reinforcing steel, including prestressing tendons, and placement		X	ACI 318: 3.5, 7.1-7.7	1910.4
2. Inspection of reinforcing steel welding:		X		
a. Verification of weldability of reinforcing steel other than ASTM A706				
b. Reinforcing steel resisting flexural and axial forces intermediate and special moment frames, and boundary elements of special reinforced concrete shear walls and shear reinforcing	X		AWS D1.4 ACI 318: 35.2	
c. Shear reinforcement	X			
d. Other reinforcing steel		X		
3. Inspect bolts to be installed in concrete prior to and during placement of concrete		X	ACI 318: 8.1.3, 21.2.8	1908.5, 1909.1
4. Inspection of anchors post-installed in hardened concrete members		X	ACI 318: 3.8.6, 8.1.3, 21.2.8	1909.1
5. Verifying use of required design mix		X	ACI 318: CH. 4, 5.2-5.4	1910.2, 1910.3
6. Sampling fresh concrete and performing slump, air content and determining the temperature of fresh concrete at the time of making specimens for strength of tests	X		ASTM C 172 ASTM C 31 ACI 318: 5.6, 5.8	1910.10
7. Inspection of concrete and shotcrete placement for proper application techniques	X		ACI 318: 5.9, 5.10	1910.6, 1910.7 1910.8
8. Inspection for maintenance of specified curing temperature and techniques		X	ACI 318: 5.11-5.13	1910.9
9. Inspection of prestressed concrete:				
a. Application of prestressing forces.	X		ACI 318: 18.20	
b. Grouting of bonded prestressing tendons in the seismic-force-resisting system	X		ACI 318: 18.18.4	
10. Erection of precast concrete members		X	ACI 318: Ch. 16	
11. Verification of in-situ concrete strength, prior to stressing of tendons in posttensioned concrete and prior to removal of shores and forms from beams and structural slabs		X	ACI 318: 6.2	
12. Inspect formwork for shape, location and dimensions of the concrete member being formed		X	ACI 318: 6.1.1	

* The inspector shall monitor all of the tasks indicated. Under the heading "Periodic", the inspector shall be present a minimum of 25% of the time, monitoring the task while it is being performed. Frequency of "periodically" inspection shall be scheduled at approximately equal intervals throughout the duration of the task. Under the heading "Continuous", the inspector shall be present 100% of the time, monitoring the task while being performed.

VERIFICATION AND INSPECTION	TABLE 2 REQUIRED VERIFICATION & INSPECTION OF STRUCTURAL STEEL			
	FREQUENCY*		REFERENCE FOR CRITERIA	
	Continuous	Periodic	REFERENCED STANDARD	
1. Material verification of high-strength bolt, nuts and washers:		X	Applicable ASTM material specifications; AISC 360, Section A3.3	
a. Identification of markings to conform to ASTM standards specified in the approved construction documents.				
b. Manufacturer's certificate of compliance required.		X		
2. Inspection of high-strength bolting:		X	AISC 360 Section M2.5	
a. Bearing-type connections.		X		
b. Slip critical connections.	X			
3. Material verification of structural steel:		X	ASTM A6 or ASTM A568	
a. Identification of markings to conform to ASTM standards specified in the approved construction documents.				
b. Manufacturer's certified mill test reports.		X		
4. Material verification of weld filler materials:		X	AISC 360 Section A3.5	
a. Identification of markings to conform to AWS specifications in the approved construction documents.				
b. Manufacturer's certificate of compliance required		X		
5. Inspection of welding:				
a. Complete and partial penetration groove welds.	X			
b. Multi-pass fillet welds	X			
c. Single-pass fillet welds $> \frac{5}{16}$ "	X		AWS D1.1	
d. Single-pass fillet welds $\leq \frac{5}{16}$ "	X			
e. Floor and Roof deck welds	X		AWS D1.3	
6. Inspection of steel frame joint details for compliance with approved construction documents:				
a. Details such as bracing and stiffening	X			
b. Member locations	X			
c. Application of joint details at each connection.	X			
7. Additional bolt & welding inspection per AISC 360-10			AISC 360 Section N	

* The inspector shall monitor all of the tasks indicated. Under the heading "Periodic", the inspector shall be present a minimum of 25% of the time, monitoring the task while it is being performed. Frequency of "periodically" inspection shall be scheduled at approximately equal intervals throughout the duration of the task. Under the heading "Continuous", the inspector shall be present 100% of the time, monitoring the task while being performed.

LEGEND & ABBREVIATIONS

TYP = TYPICAL
N.S. = NEAR SIDE
F.S. = FAR SIDE
O.C. = ON CENTER
CMU = CONCRETE MASONRY UNIT
T/ = TOP OF
CLR = CLEAR
U.N.O. = UNLESS NOTED OTHERWISE
T&G = TONGUE AND GROOVE
P.T. = PRESTRESSED TREATED
HKB = HOLLOW KINNED BOLT
C.R. = CONCRETE EXPANSION ANCHOR
LVL = LAMINATED VENEER LUMBER
PSL = PARALLEL STRAND LUMBER
GT = GIRDER TRUSS
ALT = ALTERNATE
EA = EACH
W/ = WITH
CLR COV = CLEAR COVER
(E) = EXISTING
DBA = DEFORMED BAR ANCHOR



CONCRETE PROTECTION FOR REINFORCEMENT			
IN CAST-IN-PLACE CONCRETE			
THE FOLLOWING CONCRETE COVER SHALL BE PROVIDED FOR REINFORCEMENT; UNLESS NOTED OTHERWISE			
COVER, IN.			
CONCRETE CAST AGAINST AND PERMANENTLY EXPOSED TO EARTH 3			
CONCRETE EXPOSED TO EARTH OR WEATHER #6 THROUGH #18 BARS 2			
#5 BAR, W31 OR D31 WIRE, AND SMALLER 1 1/2			
CONCRETE NOT EXPOSED TO WEATHER OR IN CONTACT WITH GROUND			
SLABS, WALLS, JOIST: #14 AND #18 BARS 1 1/2			
#11 BAR AND SMALLER 3/4			
BEAMS AND COLUMNS: PRIMARY REINFORCEMENT, TIES, STIRRUPS, SPIRALS 1 1/2			

TABLE 3B
SCASPO03B-14
REQUIRED VERIFICATION & INSPECTION OF MASONRY CONSTRUCTION (LEVEL B QUALITY ASSURANCE)


Verification of Slump flow and Visual Stability Index (VSI) as delivered to project the site in accordance with Article 1.5 B.1.b.3 for self-consolidating grout.

Verification of f_m' and f'_mc in accordance with Article 1.4 B prior to construction, except where specifically exempted by the Code.

INSPECTION TASK	TABLE 3B SCASPO03B-14 REQUIRED VERIFICATION & INSPECTION OF MASONRY CONSTRUCTION (LEVEL B QUALITY ASSURANCE)				
	FREQUENCY*		REFERENCE FOR CRITERIA		
	Continuous	Periodic	TMS 402/ ACI 530/ ASCE 5	TMS 602/ ACI 530.1/ ASCE 6	
1. Verify compliance with the approved submittals		X		Art. 1.5	
2. As masonry construction begins, verify that the following are in compliance:					
a. Proportions of site-prepared mortar		X		Art. 2.1, 2.6 A	
b. Construction of mortar joints		X		Art. 3.3 B	
c. Grade and size of prestressing tendons and anchorages		X		Art. 2.4 B, 2.4 H	
d. Location of reinforcement, connectors, and prestressing tendons and anchorages		X		Art. 3.4, 3.6 A	
e. Prestressing technique		X		Art. 3.6 B	
f. Properties of thin-bed mortar for ACC masonry	***	***		Art. 2.1 C	
3. Prior to grouting, verify that the following are in compliance:					
a. Grout space			X	Art. 3.2 D, 3.2 F	
b. Grade, type, and size of reinforcement and anchor bolts, and prestressing tendons and anchorages			X	Sec. 1.16	Art. 2.4, 3.4
c. Placement of reinforcement, connectors, and prestressing tendons and anchorages			X	Sec. 1	




TYPICAL SLAB ON GRADE CONSTRUCTION JOINT DETAIL




TYPICAL SLAB ON GRADE CONTROL JOINT DETAIL

CFDS003B




TYPICAL SLAB REINFORCING DETAILS

CFDP067




ROCK UNDERCUT AT FOOTING BEARING

NOTE: ABOVE DETAIL REQUIRED IF ROCK IS ENCOUNTERED
WITHIN 6" OF DESIGN BEARING ELEVATIONS



TYP. SECTION @ THRESHOLD MLES027A (A) S0.3


SCALE: N.T.S.



TYPICAL ISOLATION JOINT IN SLAB ON GRADE AT COLUMN

CFDD018G


NO SCALE



TYPICAL INTERIOR COLUMN FOOTING DETAIL


CFES2093

SCALE: 3/4" = 1'-0



TYPICAL STEP FOOTING DETAIL @ M E P PENETRATION


- GENERAL CONTRACTOR SHALL COORDINATE ALL INTERIOR ISOLATED & STRIP FOOTING STEPS WITH M E P LAYOUT AND SUB-CONTRACTOR(S).



TYPICAL ANCHOR ROD DETAIL

SBHD012C


SCALE: 3' = 1'-0



TYPICAL INTERIOR COLUMN IN CMU WALL DETAIL

CFES2093E


SCALE: 3/4" = 1'-0



TYP. COL IN CMU DETAIL

MOGD025A

SCALE: 1 1/2" = 1'-0




METAL STRAP DETAIL

N.T.S. @ INTERSECTING CMU WALLS


N.T.S. @ INTERSECTING CMU WALL

PROT014-E A
SO.



TYPICAL DETAIL @ BEAM BRG.

SCALE: $\frac{3}{4}$ " = 1'-0" (UNLESS OTHERWISE NOTED) MOED002X




NOTE: 42x2 REQUIRED WHERE "X" IS GREATER THAN 6"

TYPICAL STEEL JOIST CHORD


STIFFENER @ APPLIED LOADS

SCALE: NONE SRES008F




TYP. BEAM TO HSS COL. CONN.

SCALE: $1\frac{1}{2}'' = 1'-0''$ SO




TYPICAL FASTENING PATTERN FOR STEEL DECK PANELS

SRED003



TYPICAL ROOF AND FLOOR OPENING FRAME


APPLICABLE TO ROOF DRAINS, MECHANICAL UNIT OPENINGS,
AND OTHER ARCH'L/MECH'L OPENINGS. SRED003M



TYPICAL FLOOR OR ROOF OPENING FRAME DETAIL


SECTION

SCALE: $1\frac{1}{2}'' = 1'-0$ SRGS059A C S0.4




TYP. WINDOW & DOOR HEAD DETAIL – ICF WALL


SCALE: $\frac{3}{4}'' = 1'-0$



TYPICAL @ OPENINGS IN CONCRETE WALLS

NOT TO SCALE






PLAN NORTH
FOUNDATION PLAN
SCALE: 1/8" = 1'-0"

NOTES:
1. SEE SHEETS S0.1, S0.2, S0.3 AND S0.4 FOR GENERAL NOTES AND TYPICAL DETAILS
2. USGS EL. 690.00 EL. 100'-0"
3. TOP OF EXTERIOR WALL FOOTING EL. 98'-0" UNLESS NOTED OTHERWISE.

studio kremer architects

3258 Ruckriegel Parkway, Louisville, KY 40299
TEL 502.499.1100 FAX 499.1101



NELSON COUNTY SCHOOL DISTRICT
288 WILDCAT LANE
BARDSTOWN, KENTUCKY 40004

FOUNDATION PLAN

NELSON COUNTY SCHOOLS - WEST CAMPUS
THOMAS NELSON H.S.
PHASE III


2885 NEW SHEPHERDVILLE ROAD (Hwy 245) BARDSTOWN, KENTUCKY 40004

BG 15-229
DATE: 12/08/2015
DRAWN BY: JEK
CHECKED BY: TEL
REVISIONS:

2011-02

PHASE - 3

S1.1
HS




PLAN NORTH



SECURITY GRILLE PLAN

SCALE: 1/8" = 1'-0"

SCALE: 1/8" = 1'-0"



PLAN NORTH





UPPER FLOOR & MEZZANINE PLAN

SCALE: 1/8" = 1'-0"

NOTES:

1. SEE SHEETS S0.1, S0.2, S0.3 AND S0.4 FOR GENERAL NOTES AND TYPICAL DETAILS
2. W21x44(C) INDICATES COMPOSITE BEAM W/ $\frac{5}{8}$ " Ø x 3" HEADED STUDS AT 2'-0" O.C. SEE SECTION A/S5.1

<h1>UPPER FLOOR & MEZZANINE PLAN</h1>	
<p>NELSON COUNTY SCHOOLS - WEST CAMPUS</p> <p>THOMAS NELSON H.S.</p> <p>PHASE III</p>	
 <div style="display: inline-block; vertical-align: middle; text-align: center;"> <p>DESIGNED TO EARN THE ENERGY STAR</p> </div> <div style="border: 1px solid black; padding: 5px; display: inline-block; vertical-align: middle;"> <p>The estimated energy performance of this assignment meets US EPA criteria. This building will be eligible for ENERGY STAR after maintaining superior performance for one year.</p> </div>	
<p>2885 NEW SHEPHERDSVILLE ROAD (HWY 245) BARDSTOWN, KENTUCKY 40004</p>	
<p>BG 15-229</p>	
<p>DATE: 12/08/2015</p>	
<p>DRAWN BY: JEK</p>	
<p>CHECKED BY: TEL</p>	
<p>REVISIONS:</p>	
<p>2011-02</p>	
<p>PHASE - 3</p>	
<p>S2.1</p>	
<p>HS</p>	



NELSON COUNTY SCHOOL DISTRICT
 288 WILDCAT LANE
 BARDSTOWN, KENTUCKY 40004

studio kremer architects

3258 Ruckriegel Parkway, Louisville, KY 40299
 TEL 502.499.1100 FAX 499.1101

ROOF FRAMING PLAN

NELSON COUNTY SCHOOLS - WEST CAMPUS

THOMAS NELSON H.S.
 PHASE III

2885 NEW SHEPHERDVILLE ROAD (Hwy 245) BARDSTOWN, KENTUCKY 40004


BG 15-229
 DATE: 12/08/2015
 DRAWN BY: JEK
 CHECKED BY: TEL
 REVISIONS:













2011-02


PHASE - 3

S3.1

HS







NELSON COUNTY SCHOOL DISTRICT
288 WILDCAT LANE
BARDSTOWN, KENTUCKY 40004

SECTIONS & DETAILS
NELSON COUNTY SCHOOLS - WEST CAMPUS
THOMAS NELSON H.S.
PHASE III

2885 NEW SHEPHERDSVILLE ROAD (Hwy 245) BARDSTOWN, KENTUCKY 40004

BG 15-229
DATE: 12/08/2015
DRAWN BY: JEK
CHECKED BY: TEL
REVISIONS:

2011-02

PHASE - 3


S5.1

HS


studio kremer architects

3258 Ruckriegel Parkway, Louisville, KY 40299
TEL: 502.499.1100 FAX: 499.1101


CARL J.
SLESSER
110894
LICENSED
12/8/15
PROFESSIONAL ENGINEER




TYP. WINDOW OR DOOR
JAMB DETAIL - ICF WALL
SCALE: $\frac{3}{4}'' = 1'-0$




TYP. CMU SHEAR WALL BOND BM.
- ICF WALL INTERSECTION
SCALE: $\frac{3}{4}'' = 1'-0$




SECTION
SCALE: $\frac{3}{4}'' = 1'-0$




SECTION
SCALE: $\frac{3}{4}'' = 1'-0$




SECTION
SCALE: $\frac{3}{4}'' = 1'-0$




SECTION
SCALE: $\frac{3}{4}'' = 1'-0$




SECTION
SCALE: $\frac{3}{4}'' = 1'-0$



SECTION
SCALE: $1\frac{1}{2}'' = 1'-0$



DETAIL
SCALE: $1\frac{1}{2}'' = 1'-0$



SECTION
SCALE: $\frac{3}{4}'' = 1'-0$

SECTIONS & DETAILS	
THOMAS NELSON H.S. PHASE III	NELSON COUNTY SCHOOLS - WEST CAMPUS 288 WILDCAT LANE BARDSTOWN, KENTUCKY 40004

BG 15 - 229
DATE: 12/08/2015
DRAWN BY: JEK
CHECKED BY: TEL
REVISIONS:

2011-02
PHASE - 3
S5.3
HS

DESIGNED
BY
CARL J.
SLESSER
PROFESSIONAL ENGINEER
12/8/15
12/8/15
3258 Ruckriegel Parkway, Louisville, KY 40299
TEL 502.499.1100 FAX 499.1101

2885 NEW SHEPHERDSVILLE ROAD (Hwy 245) BARDSTOWN, KENTUCKY 40004

SECTION A-S6.1

Architectural section drawing A-S6.1 showing a joist seat detail on an ICF wall. The drawing illustrates the connection of a 5" deep joist to an 8" ICF wall. Key dimensions and details include:

- EXTEND JOIST TOP CHORD
- CONT. $45 \times 3 \frac{1}{2} \times 5 \frac{5}{16}$ LLV
- $3/16$ thickness of the joist top chord
- $1/2$ " thickness of the ICF wall
- $4"$ and $4"$ horizontal distances from the wall to the joist seat
- $1/4$ thickness of the joist seat
- 2 joist seats per joist
- $8"$ ICF WALL W/ #5 VERT. @ 16" O.C. AND #5 HORIZ. @ 18" O.C.
- LH-SERIES JOIST - SEE PLAN
- BRG. RL $3/8" \times 7 \frac{1}{2} " \times 9"$ W/ (2) $1 \frac{1}{2} " \phi$ x 4" LG. HEADERS STUDS @ 5" o.c.

SEE ARCH'L.

SECTION

SCALE: $\frac{3}{4}$ " = 1'-0"

CLES231E

1' - 5 $\frac{7}{8}$ "

1 1/2" METAL
ROOF DECK

DECK BRG.
EL. VARIES

8" ICF WALL W/#5 VERT.
@ 16" O.C. AND #5 HORIZ.
@ 18" O.C.

2"

VENEER

CONT. $\frac{5}{8}$ " \varnothing HILTI KB3 BOLTS
@ 24" o.c. (EMBED. 4")

SECTION

JOIST BRG. EL.
- SEE PLAN

8" ICF WALL w/
#5 HORIZ. @ 18" o.c.
& #5 VERT @ 16" o.c.

1 1/2" METAL
ROOF DECK

BRG. $\text{P}^{3/8} \times 7\frac{1}{2} \times 9"$
W/(2) $1\frac{1}{2} \times 4"$ LG. HEADED
STUDS @ 5" o.c.

LH-SERIES JOIST
- SEE PLAN

REMOVE INSULATION
AT LEDGER ANGLE

CONT. BENT $\text{P}^{3/8} \times 7" \times 7"$ w/ $5/8\text{"}$ ϕ
HILTI KB3 STAINLESS
STEEL EXP. BOLTS @
24" o.c. (EMBD. 4")

T/EXIST. ICF WALL
EL. 119'-8" ± (V.I.F.)

1' - 5 $\frac{7}{8}$ "

1/4 2
1/4 2

SCALE: $\frac{3}{4}$ " = 1'-0"

SRES1019E C S6.1

This architectural section drawing illustrates the construction of a roof deck. The top horizontal line represents the roof deck, labeled **1 1/2" METAL ROOF DECK**. Below the deck, a vertical column of **6" METAL STUDS @ 16" o.c.** supports the deck. The studs are connected to a **DEFLECTION TRACK** at the top. On either side of the central stud column, there are **LH JOIST SEE PLAN** joists. The bottom of the stud column is connected to a **STEEL BEAM SEE PLAN**. The outer edges of the stud column are reinforced with **2 1/2" METAL STUD EA. SIDE**. A note indicates a **1 1/2" GAP** between the top of the studs and the bottom of the deflection track. A dimension line shows a height of **2 1/8" VERIFY W/ARCH'L.** from the bottom of the stud column to the **EL. 118'-0" (CLEAR)** level. A callout specifies the **T/STEEL** at elevation **EL. 119'-8 1/4"**. A note on the right indicates **DECK BR EL. VARIO**. The drawing is labeled **SECTION** at the bottom left and includes a scale of **3/4" = 1'-0"** and a reference to **SRES1040A** at the bottom right.

SECTION E

NO JOIST BRACING THIS BAY

1 1/2" METAL ROOF DECK

DECK BRG.
EL. VARIES

3/16 2 2

3/16 2

LH JOIST
SEE PLAN

4 4x3x5/16 LLV
@ 8'-0" o.c.

4 2 1/2x2 1/2x1 1/4 HANGER
@ 8'-0" o.c.

1 1/2" STD. PIPE RAILS

4 5x3 TO HORIZ. 3/16

4 2 1/2x2 1/2 3/16

3/4" x 3/16" STEEL BAR GRATING

4 5x3 1/2x1 1/4 LLV

3/4" x 3/16" STEEL BAR GRATING

4 5x3 1/2x1 1/4 LLV

1'-6"

2'-0"

6"

2 1/2 3/16 3/4

WELDS AT ENDS OF BAR APPROX. 6" FR EA. END (4) PER PAN

DETAIL A-A

T/STEEL
EL. 117'-3 1/4"

3/16

3/16

4 2 1/2x2 1/2x1 1/4
@ 8'-0" o.c.

3/4" = 1'-0"

SRES1040

E

S6.1

BRG.
OM
NEL

JOIST BRG. EL.
- SEE PLAN

8" ICF WALL w/
#5 HORIZ. @ 18" o.c.
& #5 VERT @ 16" o.c.

6"

1/4 2

1/4 2

1 1/2" METAL
ROOF DECK

BRG. $P \frac{3}{8}'' \times 7 \frac{1}{2}'' \times 9''$
W/(2) $\frac{1}{2}'' \varnothing \times 4''$ LG. HEADED
STUDS @ 5" o.c.

LH-SERIES JOIS
- SEE PLAN

SECTION

SCALE: $\frac{3}{4}'' = 1'-0''$

S6.1

Architectural cross-section diagram showing a roof joist system. The diagram includes the following components and dimensions:

- JOIST BRG.** EL. SEE PLAN
- BRG. P_L 3/8" x 7 1/2" x 7 1/2"**
W/ 1/2" Ø x 4" LG. HEADED STUDS @ 5" O.C.
- K-SERIES JOIST** - SEE PLAN FOR ADD'L. INFO.
(2 1/2" DP. SEAT)
- 1 1/2" MTL. ROOF DECK**
- SEE PLAN** (referring to the top chord detail)
- CONT. 4 5x3x 1/4" LLV**
- EXTEND JOIST TOP CHORD** (1" and 2" dimensions)
- METAL PANELS**
- 8" ICF WALL W/ #5 VERT.
@ 16" O.C. & #5 HORIZ.
@ 18" O.C.**
- Detail dimensions: 1/8" and 2" for the joist top chord extension, and 3/16" and 3/16" for the top chord thickness.

SECTION

SCALE: $\frac{3}{4}'' = 1'-0''$

JOIST BEARING
EL. - SEE PLAN

EXIST. 8" ICF WALL -
REINF. NOT SHOWN

8"

4"

$\frac{1}{8}$ 2 2

K-SERIES JOIST
- SEE PLAN

$1\frac{1}{2}$ " METAL
ROOF DECK

POCKET EXIST. 8" ICF
CONC. WALL FOR JOIST
BEARING $\frac{P^3}{8} \times 4 \times 8$ - GROUT
POCKET SOLID

SRES1019G H
S6.1

SECTION SRES1040 **E**
SCALE: $\frac{3}{4}'' = 1'-0$ **S6.1**

SECTION SRES1019F 
S6.1

SECTION

SCALE: $\frac{3}{4}'' = 1'-0$ SRES1046B G S6.1

SECTIONS & DETAILS		NELSON COUNTY SCHOOL DISTRICT 288 WILDCAT LANE BARDSTOWN, KENTUCKY 40004	
NELSON COUNTY SCHOOLS - WEST CAMPUS THOMAS NELSON H.S. PHASE III		 <div style="border: 1px solid black; padding: 5px; text-align: center;"> <small>The estimated annual energy cost to heat, cool, and light this building meets the U.S. Environmental Protection Agency's ENERGY STAR® standards for energy efficiency. This building will be eligible for ENERGY STAR® after maintaining superior performance for one year.</small> </div>	
BG 15-229		2885 NEW SHEPHERDSVILLE ROAD (HWY 245) BARDSTOWN, KENTUCKY 40004	
DATE: 12/08/2015 DRAWN BY: JEK CHECKED BY: TEL REVISIONS:		2011-02	
PHASE - 3		S6.1	


BUILDING CODE INFORMATION

OCCUPANCY: USE GROUP "E" (EDUCATIONAL)
CONSTRUCTION TYPE: 2B
FIRE SPRINKLER: BUILDING SHALL HAVE FULLY AUTOMATIC SPRINKLER SYSTEM
FIRE ALARM: BUILDING SHALL HAVE FULLY INTEGRATED FIRE ALARM SYSTEM
ALLOWABLE AREA: UNLIMITED
TOTAL ACTUAL AREA: 8,536 (AUDITORIUM ONLY)
OCCUPANCY LOAD: DESIGNED FOR 703 OCCUPANTS (AUDITORIUM ONLY)
APPLICABLE CODES: KENTUCKY BUILDING CODE 2006
"FEC-1" INDICATES ABC MULTI-PURPOSE FIRE EXTINGUISHER IN RECESSED CABINET
PROVIDE 1-HOUR RATING IN THE FOLLOWING ROOMS: STORAGE P108, STORAGE P113, EQUIPMENT STORAGE P112, MECH. P202 & MECH. P203).






studio **kremmer** architects

Buckner Parkway | Louisville KY 40299

TEL 502.499.1100 FAX 499.1101



SYMBOLS LEGEND

DRAWING NUMBER		CALL-OUT TAG
SHEET NUMBER		EQUIPMENT/CASEWORK/ACCESSORY TAG
		DOOR NUMBER TAG
		ELEVATION MARKER (RELATIVE TO BUILDING)
		NORTH ARROW
Room name		ROOM TAG
ROOM NUMBER		SECTION MARKER
RAWING NUMBER		SPOT ELEVATION MARKER (RELATIVE TO FLOOR)
SHEET NUMBER		WALL TAG
		WINDOW TAG
DRAWING NUMBER		ELEVATION MARKER
SHEET NUMBER		

ON COUNTY SCHOOLS - WEST CAMPUS


WAS NELSON H.S. PHASE III

15-229


2011-02
PHASE - 3

A 0.1
HS


H



① LEVEL 1 - LIFE SAFETY PL



CONSTRUCTION DOCUMENTS



studio kremers architects
 3258 Ruckriegel Parkway, Louisville, KY 40299
 TEL: 502.249.1100 FAX: 459.1101

STUDIO KREMER
 3258 Ruckriegel Parkway, Louisville, KY 40299
 TEL: 502.249.1100 FAX: 459.1101




studio

X

studio


This architectural diagram illustrates a catwalk plan, specifically a suspended metal grating catwalk. The plan shows a long, horizontal metal grating suspended from a roof structure. The catwalk is supported by a series of vertical columns. On the left side, there is a vertical wall with insulation labeled "SOUND BATTs (TYP.)" and "A3.1". The floor below the catwalk is marked with a grid of rectangular outlines, representing room boundaries. A dimension line indicates a width of "3'-0"". The overall height of the structure is indicated as "2'-0"". The diagram includes several callout circles with labels: "1" pointing to the sound batt insulation, "2" pointing to the catwalk structure, and "A2.0" and "A3.0" pointing to specific sections of the wall and insulation. A scale bar at the bottom left indicates "1/8" = 1'-0"".

② CATWALK PLAN
1/8" = 1'-0"

WALL SCHEDULE		
Type Mark		Description
W1		ICF 8" - 5/8" IMPACT RESISTANT GYP. BD. INTERIOR - BRICK VENEER OVER BUILDING WRAP EXTERIOR
W3		ICF 8" - 5/8" IMPACT RESISTANT GYP. BD. INTERIOR - METAL PANEL OVER BUILDING WRAP EXTERIOR
W4		ICF 8" - 5/8" IMPACT RESISTANT GYP. BD. EACH SIDE
W5		8" CMU - EXTEND UP TO UNDERSIDE OF DECK
W10		2" X 4 1/2" NON-THERMAL ALUMINUM STOREFRONT SYSTEM - 1/4" CLEAR GLAZING
W11		4" CMU - EXTEND UP TO UNDERSIDE OF DECK
W15		3 5/8" STEEL STUDS @ 16" O.C. - 5/8" GYP. BD. ONE SIDE. EXTEND UP TO UNDERSIDE OF DECK
W16		6" STEEL STUDS @ 16" O.C. - 5/8" IMPACT RESISTANT GYP. BD. EACH SIDE. EXTEND UP TO UNDERSIDE OF DECK
W16.1		1-HOUR RATED, 6" STEEL STUDS @ 16" O.C. - 5/8" IMPACT RESISTANT TYPE "X" GYP. BD. EACH SIDE. EXTEND UP TO UNDERSIDE OF DECK (UL DES 419)
W23		3 5/8" STEEL STUDS @ 16" O.C. - 5/8" GYP. BD. EACH SIDE
W24		NOISE ISOLATION WALL - (2) LAYERS TYPE "X" GYP. BD. OVER ISOLATION CLIPS WITH 1" RIGID INSULATION BETWEEN CLIPS - SEE SECTION 4/A3.3 FOR MORE INFORMATION

GENERAL NOTES

1. PROVIDE BULL NOSE CMU UNITS AT ALL OUTSIDE CORNER EDGES.
2. ALL WALLS SHALL EXTEND AND SEAL TIGHT TO UNDERSIDE OF FLOOR/ROOF DECK U.N.O. (UNLESS NOTED OTHERWISE). PROVIDE INSULATION PACKED INTO METAL DECK FLUTES AS REQUIRED TO PROVIDE SOUND SEAL.
3. DIMENSION ORIGINS SHALL BE AS FOLLOWS:
 - ICF - FACE OF INSULATION
 - CMU - FACE OF CMU
 - METAL STUD - FACE OF FINISH
4. REFER TO EXTERIOR ELEVATIONS, SHEETS A2.0 FOR EXTERIOR FINISHES AND ROOM FINISH SCHEDULE, SHEET A5.0 FOR INTERIOR FINISHES.
5. REFER TO STRUCTURAL DRAWINGS FOR COLUMN SIZING, WALL REINFORCEMENT AND FRAMING MEMBERS.
6. "CG" REFERS TO CORNER GUARDS TO BE INSTALLED
7. "SS-CG" REFERS TO STAINLESS STEEL CORNER GUARDS TO BE INSTALLED UP TO 6'-0" A.F.F.
8. REFER TO SHEET A0.1 FOR MORE INFORMATION ON FIRE EXTINGUISHERS / CABINETS.
9. ALL CONCRETE SLABS ON GRADE SHALL RECEIVE A VAPOR BARRIER UNDER SLAB WITH JOINTS TAPE, PENETRATIONS SEALED AND OVERLAPS PROVIDED PER MANUFACTURERS RECOMMENDATIONS.
10. PROVIDE NEW GYPSUM BOARD FINISH ON EXISTING ICF WALLS WHERE EXTERIOR PANELS HAVE BEEN REMOVED. GYPSUM BOARD SHALL BE TO FULL HEIGHT OF WALL.



**1 AUDITORIUM MEZZANINE
1/8" = 1'-0"**

CONSTRUCTION DOCUMENTS

MEZZANINE LEVEL FLOOR PLAN

NELSON COUNTY SCHOOLS - WEST CAMPUS


THOMAS NELSON H.S.

PHASE III


DATE : 12/8/2015
DRAWN BY : BVD
CHECKED BY : SW
REVISIONS

2011-02
PHASE - 3


A 1 . 1



② LEVEL 1 REFLECTED CEILING PLATE
1/8" = 1'-0"



3 PARTIAL REFLECTED CEILING PLAN
1/8" = 1'-0"



1 ROOF PL
1/8" = 1'-0"

CONSTRUCTION DOCUMENTS

ROOF AND CEILING PLANS

IN COUNTY SCHOOLS - WEST CAMPUS

AS NELSON H.S.

PHASE II

 DESIGNED TO EARN THE ENERGY STAR

The estimated energy performance for this design meets US EPA criteria. The building will be eligible for ENERGY STAR after maintaining superior performance for one year.

SHEPHERDSVILLE ROAD (HWY 245) BARDSTOWN, KENTUCKY 40004


DATE : 12/8/2015
DRAWN BY : BVD
CHECKED BY : SW

2011-02
PHASE - 3

A 1.2

The logo for Studio Kremer Architects. It features a large, bold red 'X' mark at the top, with a small red downward-pointing triangle in the center of the 'X'. Below the 'X', the word 'studio' is written in a lowercase, black, sans-serif font. To the right of 'studio', the word 'Kremer' is written in a larger, bold, black, sans-serif font. To the right of 'Kremer', the word 'architects' is written in a lowercase, black, sans-serif font. The entire logo is set against a white background.

The logo for Studio Kremer Architects. It features a large red 'X' drawn across the page. Overlaid on this 'X' is a circular seal with a dotted outer edge. The seal contains the text 'EDWARD KREMER' at the top, 'SCOTT KREMER' at the bottom, 'REGISTERED' on the left, and 'ARCHITECT' on the right. In the center of the seal, it says 'COMMONWEALTH OF KENTUCKY' above a horizontal line, and '4734' below it. A small red 'X' is also drawn through the center of the seal.






CONSTRUCTION DOCUMENTS

EXTERIOR ELEVATIONS
NELSON COUNTY SCHOOLS - WEST CAMPUS THOMAS NELSON H.S. PHASE III 2885 NEW SHEPHERDSVILLE ROAD (Hwy 245) BARDSTOWN, KENTUCKY 40004

BG 15-229
DATE : 12/8/2015
DRAWN BY : BVD
CHECKED BY : SW
REVISIONS :

2011-02
PHASE - 3

A2.0
HS



CONSTRUCTION DOCUMENTS

BUILDING SECTIONS

NELSON COUNTY SCHOOLS - WEST CAMPUS

THOMAS NELSON H.S.

PHASE II



DESIGNED
TO EARN THE
ENERGY STAR

The estimated energy
use for this design meets
US EPA criteria. This building will
be eligible to ENERGY STAR after
maintaining superior performance
for one year.



2885 NEW SHEPHERDSVILLE ROAD (HWY 245) BARDSTOWN, KENTUCKY 40004



DATE : 12/8/2015
DRAWN BY : BVD
CHECKED BY : SW
REVISIONS :

2011-02
PHASE - 3

A3.0

Page 1 of 1





CONSTRUCTION DOCUMENTS


BUILDING SECTIONS	
NELSON COUNTY SCHOOLS - WEST CAMPUS	288 NEW SHEPHERDSVILLE ROAD (HWY 245) BARDSTOWN, KENTUCKY 40004
THOMAS NELSON H.S.	PHASE III
BG 15-229	
DATE : 12/8/2015	
DRAWN BY : BVD	
CHECKED BY : SW	
REVISIONS :	
2011-02	
PHASE - 3	
A3.1	
HS	

studio **kremer** architects

3258 Ruckriegel Parkway, Louisville, KY 40299

TEL 502.299.1100 FAX 499.1101




X studio






CONSTRUCTION DOCUMENTS	BUILDING SECTIONS
NELSON COUNTY SCHOOLS - WEST CAMPUS	
THOMAS NELSON H.S.	
PHASE III	
2885 NEW SHEPHERDSVILLE ROAD (Hwy 245) BARDSTOWN, KENTUCKY 40004	
DESIGNED TO EARN THE GREEN BIRD STAR	
DATE : 12/8/2015	DRAWN BY : BVD
CHECKED BY : SW	REVISIONS :
2011 - 02	
PHASE - 3	
A3.2	
HS	

studio **kramer** architects
3258 Ruckriegel Parkway, Louisville, KY 40299
TEL 502.249.1100 FAX 499.1101



(2) PARTIAL BUILDING SECTION
1/4" = 1'-0"



NELSON COUNTY SCHOOL DISTRICT
288 WILDCAT LANE
BARDSTOWN, KENTUCKY 40004

DESIGNED TO EARN THE
BEE'S STAGE

2885 NEW SHEPHERDSVILLE ROAD (Hwy 245) BARDSTOWN, KENTUCKY 40004


BG 15-229
DATE: 12/8/2015
DRAWN BY: BVD
CHECKED BY: SW
REVISIONS:

2011-02
PHASE - 3

A3.3
HS

12/8/2015 11:04:47 AM

CONSTRUCTION DOCUMENTS



CONSTRUCTION DOCUMENTS

WALL SECTIONS

COUNTY SCHOOLS - WEST CAMPUS

NELSON H.S.

PHASE III



DESIGNED

TO EARN THE

ENERGY STAR

The estimated energy performance for this design meets LEED criteria. The building will be eligible for ENERGY STAR after maintaining superior performance for one year.

DATE : 12/8/2015
DRAWN BY : BVD
CHECKED BY : SW

10 of 10

2011-02

A3-4

HS

3258 Ruckriegel Parkway, Louisville, KY 40299
TEL 502.499.1100 FAX 499.1101

A circular redacted stamp with the text 'COMMONWEALTH OF KENTUCKY ARCHITECTURAL REGISTRATION BOARD' around the perimeter and 'REMER' in the center.

WELSON COUNTY SCHOOL DISTRICT
288 WILDCAT LANE
BARDSTOWN, KENTUCKY 40004

TURN DOWN HARDWOOD FLOORING

25/32" X 2 1/4" HARD MAPLE FLOORING
W/ 2" FLOORING FASTENERS

3/8" CUSHION PADS @ 12" O.C.

TOP LAYER OF 15/32" SUBFLOOR LAID
AT 45 DEG. ANGLE TO BOTTOM LAYER

BOTTOM LAYER OF 15/32" SUBFLOOR LAID
PERPENDICULAR TO LONG DIMENSION OF
ROOM

LEVEL 1
100' - 0"

GYP. BD.

7/8" FURRING
STRIPS @ 16" O.C.

WALL BASE

COMPRESSIBLE BOND
BREAKER

CONCRETE SLAB

VAPOR BARRIER

4" DIA. PERF.
FOUNDATION DRAIN

CONCRETE SLAB

VAPOR BARRIER TOP AND BOTTOM'

COMPACTED GRANULAR FILL

REINFORCED CONCRETE
FOUNDATION - SEE STRUCTURAL

⑧ WALL SECTION
3/4" = 1'-0"

1 1/2" DIA. RAIL - PAINT

3/16" STAINLESS STEEL CABLE (TYP.)

1 1/2" DIA. POSTS - PAINT

1 1/2" DIA. RAIL

1/4" X 4" PLATE - WELD TO POSTS

CONCRETE SLAB

STEEL BAR JOIST

METAL DECK

ACT

4" MAX.

3'-0"

5 1/4"

AUDITORIUM MEZZANINE
111' - 8"

WELD POST TO LEDGE ANGLE (TYP.)

STEEL LEDGE ANGLE - SEE STRUCTURAL

BOND BEAM - SEE STRUCTURAL

8" CMU - PAINT

R $3\frac{1}{2}$ "

STAINLESS STEEL "ADJUST-A-JAW" TENSIONER WITH THREADED BODY AND NUT (TYP.)

1 1/2" METAL RAIL END POST

USE BEVELED STAINLESS STEEL WASHER AT STAIR LOCATIONS

PIPE SLEEVE (TYP.)

4 3/4"

4"

Technical drawing of a metal railing assembly. The railing consists of a top rail, intermediate posts, and a bottom rail. The top rail is labeled "1 1/2\" data-bbox="111 111 886 135" METAL RAILING. The intermediate posts are labeled "1 1/2\" data-bbox="111 135 886 159" METAL RAILING POST (TYP.). The bottom rail is labeled "1 1/2\" data-bbox="111 159 886 183" METAL BOTTOM RAIL (TYP.). The height of the railing is indicated as 3'-6". The drawing shows a cable run through intermediate posts, labeled "RUN CABLE THRU INTERMEDIATE POSTS (TYP.)". A note specifies "3/16\" data-bbox="111 183 886 207" STAINLESS STEEL CABLE (TYP.). A note also specifies "USE BEVELED STAINLESS STEEL WASHER AT STAIR LOCATIONS". A note specifies "STAINLESS STEEL CABLE QUICK CONNECT WITH CAP AND WASHER (TYP.)". A note specifies "NOTE: CABLE RUN LENGTHS TO 150' MAXIMUM".

WALL SECTION 1

3/4" - 1' 0"

6"

1 1/2"

2'-0"

3'-2"

3 5/8" STEEL STUDS @ 16" O.C.

ATTACH TO FACE OF CONC. RISER

WALL BASE

LEVEL 1
100' - 0"

CONCRETE SLAB

VAPOR BARRIER

SOLID SURFACE CAP

GYP. BD.

WALL BASE

CONCRETE RISER

A technical diagram illustrating a concrete staircase structure. The diagram shows a cross-section of the stairs. The top part of the diagram shows a horizontal metal deck supported by a vertical steel beam. The steel beam is connected to a vertical concrete wall. The concrete wall supports a concrete tread and riser assembly. The bottom part of the diagram shows a vertical metal deck supported by a vertical metal frame. The diagram is labeled with text and arrows: 'METAL DECK' points to the top horizontal structure, 'STEEL BEAM' points to the vertical support beam, 'CONCRETE TREAD AND RISERS' points to the concrete structure, and 'METAL DECK' points to the bottom vertical structure.

This architectural cross-section diagram illustrates a thickened slab foundation. The top portion shows a vertical wall with horizontal rebar and a thickened slab extending downwards. The slab is labeled 'THICKENED SLAB'. Below the slab, a dashed line indicates the 'LEVEL 1' elevation at '100' - 0"'. The foundation is supported by a gravel bed, and a vapor barrier is shown at the bottom. A north arrow is located in the bottom right corner.

WALL SECTION
② 3/4" = 1'-0"

METAL DECK

AUDITORIUM MEZZANINE
111' - 8"

ATTACH STUDS TO
UNDERSIDE OF DECK

Detailed description: This is a technical architectural drawing of a wall section. The top part shows a horizontal metal deck supported by vertical studs. The text 'METAL DECK' is written above the deck. The bottom part shows the studs and the text 'ATTACH STUDS TO UNDERSIDE OF DECK' with an arrow pointing to the studs. To the right, the text 'AUDITORIUM MEZZANINE' is written vertically, and below it is the dimension '111' - 8"'. A circular scale icon is located at the bottom right. The drawing is labeled 'WALL SECTION' with a circled '2' and '3/4" = 1'-0"'.

Technical diagram of a concrete wall panel with an integrated steel beam and metal deck. The panel is labeled 'ACT' and has a height of 2'-0" and a width of 2'-4". The steel beam is labeled 'STEEL BEAM' and the metal deck is labeled 'METAL DECK'.

This diagram shows a cross-section of a wall assembly. It consists of a vertical steel stud frame with horizontal cross-bracing. The left side of the wall is a smooth, light-colored surface. The right side shows the internal structure of the studs and their connections. Three callout lines point to specific parts of the wall: 'GYP. BD.' points to the top horizontal plate of the stud frame; '3 5/8" STEEL STUDS @ 16" O.C. (TYP.)' points to the studs themselves; and 'SEALANT' points to the gap between the stud frame and the smooth surface on the left.

This architectural cross-section diagram illustrates a thickened slab foundation system. The diagram shows a thickened slab resting on a carrier, which is supported by a concrete pier. The pier is constructed of 8" CMU blocks. The thickened slab is labeled 'THICKENED SLAB'. The carrier is labeled 'CARRIER'. The concrete pier is labeled '8" CMU'. The overall width of the foundation is indicated as '10' 0"'. A dimension line shows the thickness of the thickened slab as '10" C.C.'. The diagram also includes a label 'WALL BASE' pointing to the pier. A level indicator shows 'LEVEL 1 100' 0"'. The carrier is shown with a cross-hatch pattern, and the pier is shown with a vertical hatching pattern.

The diagram illustrates a cross-section of a wall. At the top, a layer of small, irregularly shaped dots represents a vapor barrier. Below the vapor barrier is a thick, light-colored rectangular block representing insulation. The bottom portion of the wall is composed of a series of vertical lines and horizontal cross-ties, representing a stud wall structure. The text 'VAPOR BARRIER' is written in capital letters to the right of the vapor barrier layer.

This technical diagram illustrates the cross-section of a mechanical penthouse roof. The assembly includes a steel joist extension, a single-ply roofing system, rigid insulation, and a metal deck. The diagram also shows spray-on acoustic insulation, steel roof trusses, and various structural and waterproofing components. Labels provide specific dimensions and material details, such as the height of 2'-0" and the width of 4'-4". The diagram is labeled "MECH PENTHOUSE 114' - 8".

Labels in the diagram:

- STEEL JOIST EXTENSION
- SINGLE-PLY ROOFING SYSTEM
- RIGID INSULATION
- COMPLETELY FILL TOP OF WALL WITH INSULATION
- METAL DECK
- 4'-4"
- STEEL ANGLE - SEE STRUCTURAL
- PRE-FINISHED METAL TRIM
- PRE-FINISHED MET GUTTER
- MECH PENTHOUSE
114' - 8
- 2'-0"
- 3-PIECE PRE-FINISHED METAL FASCIA WITH CONTINUOUS CLEATS AND DRIPS
- 3 5/8" STEEL STUD (@ 24" O.C.) FRAMING - SECURE TO JOIST EXTENSIONS
- SPRAY-ON ACOUSTIC INSULATION
- STEEL ROOF TRUSS

7 WALL SECTION
3/4" = 1'-0"

BOND BEAM - SEE STRUCTURAL

DOOR - SEE SCHEDULE

This technical diagram illustrates the cross-section of an Audit Roof. The top portion shows the roof deck with labels for 'SINGLE-PLY ROOFING' and 'RIGID INSULATION'. Below the deck, a vertical column of insulation is labeled 'SPRAY-ON ACOUSTIC INSULATION (TYP.)'. A 'DEFLECTION TRACK' is shown as a horizontal channel running along the insulation. The bottom section of the diagram shows the steel framework with 'STEEL ROOF TRUSSES -P' and '6" STEEL STUDS @ 16" O.C. SOLID BLOCKING AT 1/3 PC HEIGHT'. A callout detail 'A3.5' shows a circular opening with a diameter of 1. The total width of the roof is indicated as '125' - 4" with a compass rose symbol.

WALL SECTION
3/4" = 1'-0"

WALL BASE

CONCRETE SLAB

VAPOR BARRIER

COMPACTED GRANULAR FILL

REINFORCED CONCRETE FOUNDATION - SEE STRUCT.

SOUND BATTs

GYP. BD. EACH SIDE

7/8" FURRING @ 16" O.C.

EXTEND GYP. BD. DOWN TO WALL BASE

AUDIT PIT
98' - 4 1/2"

CONCRETE SLAB

LEVEL 1
100' - 0"

5

This technical diagram illustrates a cross-section of a concrete foundation and slab system. The diagram shows a concrete slab resting on a concrete pad, which is supported by a reinforced concrete footing. The foundation is surrounded by a perimeter insulation system and a compacted granular fill base. Key components labeled include:

- COMPRESSIBLE BOND BREAKER
- VAPOR BARRIER
- CONCRETE SLAB
- 2" PERIMETER INSULATION
- COMPACTED GRANULAR FILL
- REINFORCED CONCRETE FOOTING AND FOUNDATION - REFER TO STRUCTURAL DRAWINGS
- CONCRETE PAD
- 4'-0"
- DOWN SPOUT BEYOND

At the bottom of the diagram, a circular callout indicates a scale of $3/4" = 1'-0"$. The label "A3.4/9 - LOADING" is also present at the bottom.



studio kramer architects

3258 Ruckriegel Parkway, Louisville, KY 40299
TEL 502.249.1100 FAX 499.1101

NELSON COUNTY SCHOOL DISTRICT
288 WILDCAT LANE
BARDSTOWN, KENTUCKY 40004

STAIR / LADDER SECTIONS
NELSON COUNTY SCHOOLS - WEST CAMPUS
THOMAS NELSON H.S.
PHASE III
2885 NEW SHEPHERDSTOWN ROAD (HWY 245) BARDSTOWN, KENTUCKY 40004

BG 15-229
DATE : 12/8/2015
DRAWN BY : BVD
CHECKED BY : SW
REVISIONS :

2011-02
PHASE - 3

A3.5
HS

CONSTRUCTION DOCUMENTS

