

DANNY CLEMENS, DIRECTOR

GEORGE BROCK, MAINTENANCE SUPERVISOR THOMAS STOKES, CUSTODIAL SUPERVISOR ANDREA ROCK, ENERGY MANAGER

DEPARTMENT OF FACILITIES

MEMO

TO:

Dr. Jesse Bacon, Superintendent 978

FROM:

Danny Clemens, Director of Facilities

Date:

September 15, 2023

RE:


Lebanon Junction Elementary Road Addition DC

Lebanon Junction Elementary School has requested a 12ft wide road that will connect the Splash Park parking lot to their main school parking lot. Currently traffic is very congested entering and exiting the school on Preston Highway. This addition will help improve the traffic pattern of their car rider line. This project will be paid through Maintenance Department funds.

I recommend approval of this request.

OUR MISSION IS TO INSPIRE AND EQUIP OUR STUDENTS TO SUCCEED IN LIFE BULLITT COUNTY PUBLIC SCHOOLS IS AN EQUAL EDUCATION AND EMPLOYMENT INSTITUTION

More



Louisville 502-899-2086 • E-town 270-737-0007 • Shep. 502-543-1441 • So. Ind. 812-280-1010 • Corydon 812-738-8888

Date 9-13-23		CE AND AGREEMENT	Guaranteed 1 year	
In Account with			No Guarantee 1	
		Phone #		
Terms:		Completion Date:		
The undersigned agrees to furnish	all materials and labor	necessary for the work on the	premises located at:	
Street# 10920 S. Prest	on Hwy.	city_Lebano	n Jct. State Kv	
The undersigned property owners a	agree upon completion	of work to pay the sum of \$_	3.575	
Payment to be made in full- DEPOS				
		(Any cancellation 30% of cost		
We are not responsible for anything un control, power steering marks, scuff maguarantee is null and void if driveway is Job:	arks, vegetation growth. A s sealed by any other con	my damage due to heavy equipr	ment is not guaranteed. This tials:	
RESURFACING Resurface to prepare old asphalt vegetation from edges, spray with Repair broken areas and wedge Lay approximately 15 of horizontal transpedges at a 45 degree angles.	n grass and weed kiler. low spots as needed. lot mix asphalt.	 top and roll for compaction 	oroximately 6" to 8" deep. o crushed stone. l killer of hot mix black on.	
 Resurface to prepare old asphalt vegetation from edges, spray with Repair broken areas and wedge left by approximately 15 of head 	n grass and weed kiler. low spots as needed. lot mix asphalt. le for proper finish. lo prepare for paving. lone as needed and roll	Remove dirt or grass apple Lay approximatelyto Spray with grass & weed Lay approximately top and roll for compaction to the compact of	oroximately 6" to 8" deep. of hot mix black oroximately 6" to 8" deep. oroximately 6" deep. oroximately	
 Resurface to prepare old asphalt vegetation from edges, spray with Repair broken areas and wedge Lay approximately 15 of h Tamp edges at a 45 degree angle FOR GRAVEL AREA Remove vegetation from edges to Grade existing gravel and add sto base for compaction. Spray with grass & weed killer. Lay approximately 2 inche top and roll for compaction. 	n grass and weed kiler. low spots as needed. lot mix asphalt. le for proper finish. o prepare for paving. one as needed and roll S of hot mix black le for proper finish.	Remove dirt or grass apple Lay approximatelyto Spray with grass & weed Lay approximately top and roll for compaction top and roll for any edges at a 45 deg FOR REMOVAL AND In the Remove old blacktop or the compact of the compac	croximately 6" to 8" deep. crushed stone. l killer. of hot mix black on. ree angle for proper finish. REPLACEMENT concrete. to of stone base and le and roll base for compaction. l killer. of hot mix black on. ree angle for proper finish.	
Resurface to prepare old asphalt vegetation from edges, spray with Repair broken areas and wedge Lay approximately 1.5 of how Tamp edges at a 45 degree angle FOR GRAVEL AREA Remove vegetation from edges to Grade existing gravel and add sto base for compaction. Spray with grass & weed killer. Lay approximately 2 inche top and roll for compaction. Tamp edges at a 45 degree angle SEAL COATING Entire asphalt area to be cleaned High pressure seal coat.	n grass and weed kiler. low spots as needed. lot mix asphalt. le for proper finish. o prepare for paving. one as needed and roll S of hot mix black le for proper finish.	Remove dirt or grass apple Lay approximatelyto Spray with grass & weed Lay approximately top and roll for compaction top and roll for compaction of the compact	croximately 6" to 8" deep. crushed stone. l killer. of hot mix black on. ree angle for proper finish. REPLACEMENT concrete. to of stone base and le and roll base for compaction. l killer. of hot mix black on. ree angle for proper finish.	