

MOLD SCREENING AND PROTOCOL REPORT

Anchorage Public School 11400 Ridge Rd, Louisville, KY 40223 Project # 25-0284-32

Survey Date: May 27, 2025

Report Date: June 4, 2025



MOLD SCREENING & PROTOCOL REPORT

Section 1 General:

Subject: Mold Screening and Protocol Report

Date: 5/27/2025 **Time**: 11:30 AM

Location: Anchorage Public Schools, 11400 Ridge Rd, Anchorage, KY 40223

Client: Anchorage Public Schools

Property Contact:

Inspector: Andrew Peters

Inspector's Company Address: Metric Environmental

3701 Taylorsville Road, Suite 1

Louisville, KY 40220

Section 2 Method:

- Visual inspection of Break Room and adjacent areas of facility based on the Indoor Environmental Standards Organization, *Standards of Practice for the Assessment of Indoor Environmental Quality*.
- 4 Micro-5 air samples throughout the assessment, 1 inside Rooms 201, 121, 105, 1 outside of the building, and 1 blank sample
- 1 Tape Sample inside the crawlspace inside Room 105



Section 3 Findings:

Amplified indoor mold spore counts were detected as follows: location and list of amplified spore types detected on sample. "Amplification" means higher than outdoor baseline; unless inspector/analyst renders opinion to the contrary

• Crawlspace Under Room 201: Aspergillus/Penicillium (High), Chaetomium (Medium), Botrytis (High), Acremonium (High)

Generally, indoor airborne fungal levels should be similar to or lower than the levels outside, and the predominant fungal genera (type of fungi) should be similar between inside and outside the building. When fungal levels inside a building are significantly higher (e.g. 10x) than outdoor levels, then fungal growth may be occurring inside the building. Oftentimes, fungal levels on testing inside may be slightly higher than outside, due to higher outdoor fungal levels the previous day. Outdoor fungal levels fluctuate more frequently outside compared to inside, where air is recirculated and filtered (unit ventilators) inside building. The amount of fresh outside air supply in the home also influences indoor fungal levels. Background levels are considered to be 1-5 spores by raw count.

Several areas had slightly elevated mold spore levels compared to outside or typical background levels. These areas should be retested when the other remediation areas are tested after remediation has occurred. These areas were:

• Room 105: Aspergillus/Penicillium (elevated),



Section 4 Discussion:

- It was reported that the toilet had water leaks in Room 201 and was discovered in May 2025.
- The area around the toilet has evidence of water damage. Staining was present on baseboards and floor tiles were losing adhesion to the subfloor.
- The subfloor had some flexing and instability indicating a prolonged water leak.
- The underside of the subfloor was discolored when viewed from the crawlspace. Mold growth was observed from the crawlspace. Pooling water was present above the vapor barrier under the water leak.
- The wood panel wall on the exterior wall of Room 201 was warped and soft from previous water damage. At the time of inspection, the wood paneling was dry.
- The crawlspace is accessed from room 105. Room 105 had slightly elevated Aspergillus levels in the air. Improved sealing from the class room to the crawlspace is recommended.
- In the middle of the crawlspace, there was pooling water under the vapor barrier. The slope of the soils under the vapor barrier do not allow for water coming from the known water leak to reach where the water under the vapor barrier is located by ground movement. There could be a second source of moisture in the crawlspace. An inspection during heavy rain is recommended to see if water is coming in from heavy rain or if there is an internal leak. No moisture on walls or joists was detected other than the area of the known leak at the time of inspection. It is possible the water from the known leak flowed along the above subfloor floor and was deposited in the middle of the crawlspace. It is recommended to fix the known leak of the toilet, remove any water in the crawlspace, occasionally inspect the crawlspace for additional water, determine if the known leak of the toilet is the source of the water in the center of the crawlspace, if the water returns after the remediation of the known leak.
- An air sample was taken in the area of previous remediation in room 121. That sample was well below outdoor levels. Walls at the time of inspection were dry.



• HVAC condensate lines dripped at the foundation of the building. It is recommended that the condensate lines drain at least 5 feet from the foundation of the building.

Section 5 Conclusions:

Is remediation needed? YES

Please see section 6 and table 4 for further details.

The remediation can involve a multi-step process to adequately remove the mold contamination. The process begins with proper removal of visible mold growth. After all visible mold growth has been removed, air samples are collected in the work areas. If the mold levels for all spore types are similar or lower to those found outside, the remediation is considered acceptable. If the air samples are not acceptable, then additional remediation is required. At this point, destructive exploration may have to be performed to find hidden or concealed areas of mold growth. This would include searching in areas adjacent to where removal of water damaged drywall and wood paneling had already occurred. Air sampling would be performed after any additional work or phase is performed and continued until similar or lower levels of spores are found inside compared to outside.

Since remediation is needed, based on the results of this mold screening investigation, Metric Environmental offers the following:

Remediation Proposal

Mold remediation should be performed by a trained and qualified mold remediation professional. Contact a licensed/certified mold remediation professional to perform the mold remediation.

The remediation proposal needs to document all contractor information and credentials.

All remediation proposal activities, specifics, methodology and location(s) to be remediated should be clearly detailed in the proposal.



As part of their remediation proposal, the remediation company should provide a written warranty for successful remediation verified in passing third party clearance testing.

All quantities should be verified on site by the remediation company.



Section 6 Remediation Procedure

Recommendations – The following areas are in need of remediation following moisture source correction: See guidelines and protocol below.

Crawlspace and Room 201 – Remove affected flooring (floor tile, etc.) and affected drywall and wood, inspect the subfloor or structural integrity – Replace if needed. Remove standing water from crawlspace. Disinfect the areas. Non-porous surfaces can be cleaned.

Air should be HEPA filtered throughout the area prior to, during, and following remediation to ensure the indoor mold levels are lowered to acceptable levels when compared to outdoors.

As part of their remediation proposal, the remediation company should provide a written warranty for successful remediation verified in passing third party clearance testing.

Refer to Table 4 for a list of affected building materials, estimated quantities, and recommendations for remediation. All quantities should be verified on site by the remediation company.

PLEASE SEE SECTION 7 FOR KENTUCKY MOLD REGULATIONS.



Section 7 Kentucky Regulations:

Mandatory

Follow all protocols and procedures outlined in 40 KAR 2:330. Mold remediation.

Link below to download to find required mold remediation procedures and forms:

https://apps.legislature.kv.gov/law/kar/titles/040/002/330/

https://www.ag.ky.gov/Resources/Pages/forms.aspx

Mold Forms Include:

• EPA Mold Guide K-02-003 - A Brief Guide to Mold, Moisture, and Your Home

Read and sign below documents prior to mold removal.

- Kentucky Mold Remediation Form MRC-1 Read This About Mold Before You Sign a Contract (October 2012)
- Kentucky Mold Remediation Form MRC-2 Read This About Indoor Environmental Professionals Before You Sign a Contract (October 2012)
- Kentucky Mold Remediation Form MRC-3 Notice of Moisture Problem (October 2012)
- Kentucky Mold Remediation Form MRC-4 Commercial or Institutional Customer (October 2012)



Section 8 References:

1 - The American Society of Heating, Refrigerating, and Air Conditioning Engineers (ASHRAE) has determined that acceptable ranges of temperature and relative humidity for the summer and winter are:

Relative Humidity	Winter Temperature	Summer Temperature
30 %	69.0°F - 78.0°F	76.0°F - 82.0°F
60 %	68.0°F - 75.0°F	74.0°F - 78.0°F

These standards apply for persons clothed in typical summer and winter clothing, at light, mainly sedentary activity. Source: Adapted from the ANSI/ASHRAE Standard 55-2017, *Thermal Environmental Conditions For Human Occupancy*.

- 2 ANSI/ASHRAE Standard 62.1-2016, *Ventilation for Acceptable Indoor Air Quality*, suggests that carbon dioxide levels be maintained at or below 700 ppm above the outside level to keep bioeffluents (body odor) within an acceptable level. The OSHA Permissible Exposure Limit for carbon dioxide is 5000 ppm.
- 3 2025 Threshold Limit Value (TLV) of the American Conference of Governmental Industrial Hygienists for carbon monoxide is 25 ppm. The OSHA Permissible Exposure Limit for carbon monoxide is 50 ppm.
- 4 *Investigating Fungal Contamination in Buildings*, EMLab P & K, 2003, states that in general, indoor concentrations of fungi and bacteria should be lower than outdoor levels.
- 5 In the OSHA Technical Manual, OSHA considers indoor surface samples of 1,000,000 CFU/in² or indoor air sample results of 1,000 CFU/m³ as an indication of contamination. OSHA Technical Manual, Chapter 2.



Section 9 Limitations and Signature

Limitations

The information contained in this report has been obtained through conversations, sampling and survey. The evaluation, conclusions and recommendations of this report are based solely upon the conditions present at the facility during the sampling period. Although great care has been taken by Metric Environmental in compiling and checking the information contained in this report to ensure that it is current and accurate, Metric Environmental disclaims any and all liability for any errors, omissions or inaccuracies in such information and data, whether attributable to inadvertence or otherwise, and for any consequence arising therefrom. The data provided hereunder neither purports to be nor constitutes legal or medical advice. Metric Environmental shall not be liable for any special, consequential or exemplary damages resulting, in whole or in part, from customers use of the data. Liability on the part of Metric Environmental is limited to the monetary value paid for this report.



Respectfully,

Douglas W. Peters, CIH, CSP

Dough W Pets

Certified Industrial Hygienist / Project Manager



Tables ATTACHMENT 1



Table 1. Summary of Results of Mold Analysis of Air Samples Anchorage Public Schools 11400 Ridge Rd, Louisville, KY 40223

MICRO 5 CASSETTE AIR SAMPLES							
Room/Area Description	Sample Number	Results Spore Density or Concentration/Predominant Genus					
Room 201	MC5-001	3,300 spores/m3	Ascospores (600) Basidiospores (2,100) Cladosporium (600)				
Room 105	MC5-002	3,300 spores/m3	Ascospores (200) Aspergillus/Penicillium ⁺⁺ (600) Basidiospores (2,100) Cladosporium (200) Myxomycetes ⁺⁺ (200)				
Room 121	MC5-003	800 spores/m3	Aspergillus/Penicillium ⁺⁺ (200) Basidiospores (600)				
Outdoors	MC5-004	11,800 spores/m3	Ascospores (2,600) Basidiospores (8,800) Cladosporium (400)				

^{*} **Bold** Genus represents fungal levels at an elevated level when compared to the outdoor sample or typical background levels.

Table 2. Summary of Results of Microscopic Analysis of Surface Bulk Samples Anchorage Public Schools 11400 Ridge Rd, Anchorage, KY 40223

TAPE LIFT SAMPLES							
Room/Area Description	Sample Results Number Colony Forming Units (CFU) / mL						
Room 105 Crawlspace Subfloor	TP-001	High High *High* Medium	Acremonium ⁺⁺ Aspergillus/Penicillium ⁺⁺ Botrytis Chaetomium ⁺⁺				

^{*} Bold Bacteria levels at an elevated level when compared to the typical background levels.



Tables 3. Summary of Results of Air Parameter Readings Anchorage Public Schools 11400 Ridge Rd, Louisville, KY 40223

Metric Environmental used direct reading instrumentation to measure standard IAQ parameters. Listed in the table below are the readings collected on-site:

Location	Temperature (deg F)	Humidity (rH%)
Room 201	76.0	62
Room 105	73.0	56
Room 121	72.0	56
Crawlspace	79.0	66
Outdoors	66.0	73

^{*} Bold numbers indicate readings that are above the ASHRAE recommended guidelines.

Temperature was within acceptable limits within occupied areas. Relative humidity (rH) was above acceptable limits. It can be expected that humidity levels will fluctuate in the area. It will be important to keep humidity levels below 60% rH. Humidity levels should range between 30% and 60% rH.



Tables 4. Summary of Affected Building Materials Anchorage Public Schools 11400 Ridge Rd, Louisville, KY 40223

Location	Area Affected
Room 201 Restroom area Remove affected floor tiles. Removed affected wood and drywall. Clean and disinfect subfloor – if the subfloor has lost structural integrity, it should be removed and replaced.	64 sqft
Room 105 crawlspace Remove standing water under leak and in the center of the crawlspace. Clean and disinfect and encapsulate the subfloor. If the subfloor has lost structural integrity, remove and replace.	81 sqft



Laboratory Reports ATTACHMENT 2



EMSL Analytical, Inc.

6340 CastlePlace Dr. Indianapolis, IN 46250 Tel/Fax: (317) 803-2997 / (317) 803-3047

http://www.EMSL.com / indianapolislab@emsl.com

EMSL Order: 162506782 **Customer ID:** ENMG50 **Customer PO:** 25-0284-32

Project ID:

(502) 454-8530

Phone:

Attention: Doug Peters

 Metric Environmental
 Fax:
 (502) 454-8528

 3701 Taylorsville Road
 Collected Date:
 05/27/2025

 Suite 1
 Received Date:
 05/28/2025

 Louisville, KY 40220
 Analyzed Date:
 05/29/2025

Project: 25-0284-32 ANCHORAGE PUBLIC SCHOLLS 11400 RIDGE ROAD

Test Report: Microscopic Examination of Fungal Spores, Fungal Structures, Hyphae, and Other Particulates from Tape Samples (EMSL Method MICRO-SOP-200)

Lab Sample Number	Client Sample ID	Location	Fungal Identification	Category
162506782-0001	TP-001	ROOM 105 CRAWLSPACE SUBFLOOR	Acremonium++	High
			Aspergillus/Penicillium++	High
			Botrytis	*High*
			Chaetomium++	Medium

No discernable field blank was submitted with this group of samples.

Report Comment:

Bipolaris++ = Bipolaris/Drechslera/Exserohilum Myxomycetes++ = Myxomycetes/Periconia/Smut
* = Sample contains fruiting structures and/or hyphae associated with the spores.

Denotes Not Detected.

Category	Count/area analyzed
Medium	1 to 10 11 to 100 101 to 1000 > 1000

Zachary Beals, Lab Manager or other Approved Signatory

EMSL maintains liability limited to cost of analysis. Interpretation and use of test results are the responsibility of the client. This report relates only to the samples reported above and may not be reproduced, except in full, without written approval by EMSL. EMSL bears no responsibility for sample collection activities or analytical method limitations. The report reflects the samples as received. Results are generated from the field sampling data (sampling volumes and areas, locations, etc.) provided by the client on the Chain of Custody. Samples are within quality control criteria and met method specifications unless otherwise noted.

Samples analyzed by EMSL Analytical, Inc. Indianapolis, IN AIHA LAP, LLC-EMLAP Accredited #157245

Initial report from: 05/29/2025 03:17 PM



EMSL Analytical, Inc.

6340 CastlePlace Dr. Indianapolis, IN 46250 Tel/Fax: (317) 803-2997 / (317) 803-3047

http://www.EMSL.com / indianapolislab@emsl.com

Project ID:

Attention: Doug Peters Phone: (502) 454-8530

 Metric Environmental
 Fax:
 (502) 454-8528

 3701 Taylorsville Road
 Collected Date:
 05/27/2025

 Suite 1
 Received Date:
 05/28/2025

Louisville, KY 40220 Analyzed Date: 05/29/2025

Project: 25-0284-32 ANCHORAGE PUBLIC SCHOLLS 11400 RIDGE ROAD

Test Report: Micro-5(™) Analysis of Fungal Spores & Particulates by Optical Microscopy (Methods MICRO-SOP-201, ASTM D7391)

Lab Sample Number: Client Sample ID: Volume (L): Sample Location:	162506782-0002 MC5-001 25 ROOM 201		1	62506782-0003 MC5-002 25 ROOM 105		,	162506782-0004 MC5-003 25 ROOM 121		
Spore Types	Raw Count†	Count/m³	% of Total	Raw Count†	Count/m³	% of Total	Raw Count†	Count/m³	% of Total
Alternaria (Ulocladium)	-	-	-	-	-	-	-	-	-
Ascospores	7	600	18.2	3	200	6.1	-	-	-
Aspergillus/Penicillium++	-	-	-	8	600	18.2	2	200	25
Basidiospores	26	2100	63.6	26	2100	63.6	7	600	75
Bipolaris++	-	-	-	-	-	-	-	-	-
Chaetomium++	-	-	-	-	-	-	-	-	-
Cladosporium	7	600	18.2	3	200	6.1	-	-	-
Curvularia	-	-	-	-	-	-	-	-	-
Epicoccum	-	-	-	-	-	-	-	-	-
Fusarium++	-	-	-	-	-	-	-	-	-
Ganoderma	-	-	-	-	-	-	-	-	-
Myxomycetes++	-	-	-	2	200	6.1	-	-	-
Pithomyces++	-	-	-	-	-	-	-	-	-
Rust	-	-	-	-	-	-	-	-	-
Scopulariopsis/Microascus	-	-	-	-	-	-	-	-	-
Stachybotrys/Memnoniella	-	-	-	-	-	-	-	-	-
Unidentifiable Spores	-	-	-	-	-	-	-	-	-
Zygomycetes	-	-	-	-	-	-	-	-	-
Total Fungi	40	3300	100	42	3300	100	9	800	100
Hyphal Fragment	-	-	-	-	-	-	-	-	-
Insect Fragment	-	-	-	-	-	-	-	-	-
Pollen	-	-	-	-	-	-	-	<u>-</u>	_
Analyt. Sensitivity 600x	-	80	-	-	80	-	-	80	-
Analyt. Sensitivity 300x	-	40*	-	-	40*	-	-	40*	-
Skin Fragments (1-4)	-	3	-	-	3	-	-	2	-
Fibrous Particulate (1-4)	-	2	-	-	2	-	-	2	-
Background (1-5)	-	2	-	-	3	-	-	2	-

Zachary Beals, Lab Manager or other Approved Signatory

EMSL Analytical, Inc. maintains liability limited to cost of analysis. Interpretation and use of test results are the responsibility of the client. This report relates only to the samples reported above, and may not be reproduced, except in full, without written approval by EMSL Analytical, Inc. EMBLA Analytical, inc. EMBLA Analytical, inc. Early or sample collection activities or analytical method limitations. The report reflects the samples are received. Results are generated from the field sampling data (sampling data (sampling volumes and areas, locations, etc.) provided by the client on the Chain of Custody. Samples are within quality control criteria and met method specifications unless otherwise noted. Skin Fragment and Fibrous Particulate ratings are based on the percent of non-fungal material they represent: 1 (1-25%), 2 (26-50%), 3 (51-75%), or 4 (76-100%). Background ratings are based on the total area covered by non-fungal particiles: 1 (1-25%), 2 (26-50%), 3 (51-75%), 4 (76-99%), or 5 (100%; overloaded). High levels of background particulates, leading to underestimation. Background levels of 5 indicate an overloading of background particulates, prohibiting accurate detection and quantification. Present = Spores detected on overloaded samples. Results are not blank corrected unless otherwise noted. The detection limit is equal to one fungal spore, structure, pollen, fiber particle or insect fragment. "*" Denotes particles found at 300X. "." Denotes not detected. Due to method stopping rules, raw counts >= 100 are extrapolated based on the percentage analyzed.

Samples analyzed by EMSL Analytical, Inc. Indianapolis, IN AIHA LAP, LLC-EMLAP Accredited #157245

Initial report from: 05/29/2025 03:17 PM

⁺⁺ Includes other spores with similar morphology; see EMSL's fungal glossary for each specific category.

[†] Due to method stopping rules, extrapolated raw counts are reported in parenthesis.



EMSL Analytical, Inc.

6340 CastlePlace Dr. Indianapolis, IN 46250 Tel/Fax: (317) 803-2997 / (317) 803-3047

http://www.EMSL.com / indianapolislab@emsl.com

Project ID:

 Attention:
 Doug Peters
 Phone:
 (502) 454-8530

 Metric Environmental
 Fax:
 (502) 454-8528

 3701 Taylorsville Road
 Collected Date: 05/27/2025

 Suite 1
 Received Date: 05/28/2025

 Louisville, KY 40220
 Analyzed Date: 05/29/2025

Project: 25-0284-32 ANCHORAGE PUBLIC SCHOLLS 11400 RIDGE ROAD

Test Report: Micro-5(™) Analysis of Fungal Spores & Particulates by Optical Microscopy (Methods MICRO-SOP-201, ASTM D7391)

Lab Sample Number: Client Sample ID: Volume (L): Sample Location:	: MC5-004 : 25			62506782-0006 MC5-005 BLANK					
Spore Types	Raw Count†	Count/m ³	% of Total	Raw Count†	Count/m³	% of Total	-		
Alternaria (Ulocladium)	-	-	-	-	-	-			
Ascospores	33	2600	22	-	-	-			
Aspergillus/Penicillium++	-	-	-	-	-	-			
Basidiospores	100(110)	8800	74.6	-	-	-			
Bipolaris++	-	-	-	-	-	-			
Chaetomium++	-	-	-	-	-	-			
Cladosporium	5	400	3.4	-	-	-			
Curvularia	-	-	-	-	-	-			
Epicoccum	-	-	-	-	-	-			
Fusarium++	-	-	-	-	-	-			
Ganoderma	-	-	-	-	-	-			
Myxomycetes++	-	-	-	-	-	-			
Pithomyces++	-	-	-	-	-	-			
Rust	-	-	-	-	-	-			
Scopulariopsis/Microascus	-	-	-	-	-	-			
Stachybotrys/Memnoniella	-	-	-	-	-	-			
Unidentifiable Spores	-	-	-	-	-	-			
Zygomycetes	-	-	-	-	-	-			
Total Fungi	148	11800	100	-	No Trace	-			
Hyphal Fragment	-	-	-	-	-	-			
Insect Fragment	-	-	-	-	-	-			
Pollen	-	-	-	-	-	-	_	-	-
Analyt. Sensitivity 600x	-	80	-	-	0	-	-	-	-
Analyt. Sensitivity 300x	-	40*	-	-	0*	-			
Skin Fragments (1-4)	-	2	-	-	-	-			
Fibrous Particulate (1-4)	-	2	-	-	-	-			
Background (1-5)	-	2	-	-	-	_			

Zachary Beals, Lab Manager or other Approved Signatory

EMSL Analytical, Inc. maintains liability limited to cost of analysis. Interpretation and use of test results are the responsibility of the client. This report relates only to the samples reported above, and may not be reproduced, except in full, without written approval by EMSL Analytical, Inc. EMBLA Analytical, inc. EMBLA Analytical, inc. Early or sample collection activities or analytical method limitations. The report reflects the samples are received. Results are generated from the field sampling data (sampling data (sampling volumes and areas, locations, etc.) provided by the client on the Chain of Custody. Samples are within quality control criteria and met method specifications unless otherwise noted. Skin Fragment and Fibrous Particulate ratings are based on the percent of non-fungal material they represent: 1 (1-25%), 2 (26-50%), 3 (51-75%), or 4 (76-100%). Background ratings are based on the total area covered by non-fungal particiles: 1 (1-25%), 2 (26-50%), 3 (51-75%), 4 (76-99%), or 5 (100%; overloaded). High levels of background particulates, leading to underestimation. Background levels of 5 indicate an overloading of background particulates, prohibiting accurate detection and quantification. Present = Spores detected on overloaded samples. Results are not blank corrected unless otherwise noted. The detection limit is equal to one fungal spore, structure, pollen, fiber particle or insect fragment. "*" Denotes particles found at 300X. "." Denotes not detected. Due to method stopping rules, raw counts >= 100 are extrapolated based on the percentage analyzed.

Samples analyzed by EMSL Analytical, Inc. Indianapolis, IN AIHA LAP, LLC-EMLAP Accredited #157245

Initial report from: 05/29/2025 03:17 PM

⁺⁺ Includes other spores with similar morphology; see EMSL's fungal glossary for each specific category.

[†] Due to method stopping rules, extrapolated raw counts are reported in parenthesis.

METRIC Mattre Environment	OrderID: 162506782			
METRIC Wetric Entritromental LLC Special Note: Control	250 6783 Lab Use-WO# Acct #	502-454-8530 Send Results to: dougp@MetricEnv.com	NOTE: All samples for organics should be kept at 4°C from collection untit testing. Schedule rush analyses in advance. Indicate preservatives added & media type. Indicate analysis method for organics tests. NOTE: All samples for organics test at 4°C from collection untit testing. Schedule rush analyses in advance. Indicate analysis method for organics tests. NO Option	× × × s return requested at temp [] Cool [] IR[] IS
METTRIC Metric Envritormental LLC Sepecial for the continuous		X	leis Mētāls-Fxtract pro-Fxtract Am Metals II (w/ organics) M Total AirVol M Consol	25 25 25 25 25 27/25 19:16
METTRIC Metric Envritormental LLC Sepecial for the continuous	ta package	Kentu	19)	5 5 5 5-Outside Are
Metric Environmental LLC Metric Environmental LLC	reporting or da		Select/ALL/that/App Bülk//Asp D nt Count) ve only) 1/4/8 interm) i) ESTOS AIR: RATOR SECTOS AIR: RATOR	5 5 5 Inside Area OA= Date/Time
Metric Envirormental LLC	Il Notes:	LLECTED	Frests (Analytes) Frests (Analytes) Frum (EPA 600 Frum (EPA 700 Frum (EP	
MCS-006 5/28/25 MCS-006 Metric Envirorrement	Specification of the state of t	S WERE CO	00 (2) (2) (2) (3) (4) (4) (4) (4) (4) (4) (4) (4) (4) (4	
Project Na Project Lou Project Lou Project Lou Project Lou Project Lou Purchase (1 148 hours (1 148 hours (1 154 hours (1	mental LLC 1, Louisville, KY 40220 502)454-8528 4,com Special Instructions finc	STATE WHERE SAMPLE		21 21 21 Signature Signature Signature Signature Signature
Project Na Project Lou Purchase (1 148 hours (1 154 hours (1 15	Metric Envriror 1 Taylorsville Road, Suite (502)454-8530 * Fax (www.MetricEn	0 Ridge Road 5-0284-32 5-0284-32	rix/Sample/Pec/Select_ONE) pples on form should be of SAM 22. Use additional forms as nee [1 Waste [1 Waste [1 Waste [1 Waste [1 Wayte, Drinking ar (TSP) [1 Compliance ar (TSP) [1 Wipe [1 Hex. Chromium [X] Tape LIft [1] [1] [1]	Room 105 Crawl Room 105 Crawl Room Room Room Room Room Room Room Roo
Project Na Project Lou Project Lou Project Lou Project Lou Project Lou Purchase (1 148 hours (1 148 hours (1 154 hours (1	NTAL 370'	1140	All solutions of the so	Andrew & And
Project Na Project Low Project Low Project Low Project Low Purchase (1 16-8 hours (1 172 hours (1 174 hours (T N N N N N N N N N N N N N N N N N N N	on: Br: Br No.:		5/28/25 5/28/25 5/28/25 5/28/25 5/28/25 5/28/25 5/28/25 3/28/25 3/28/25 3/28/25 3/28/25 3/28/25 3/28/25 3/28/25 3/28/25
	E X Froject Name:	Project Locati Project Numb Purchase Ord	16-8 hours 16-8 hours 15-8 hours 172 hours 174 hours 1	MC5-001 MC5-002 MC5-003 MC5-004 MC5-005 MC5-005 Sampled by [Sampled by [Received in k



Supplemental Documents ATTACHMENT 3





The area from which the leak originated. Some water staining is present around the toilet and around edges of the floor tiles.





Water staining around the toilet.






The affected area.





Underside of the subfloor of the affected area. Water staining and mold growth are present.





Underside of the subfloor. Water staining and mold growth are present.





Standing water in the crawlspace under the affected area.





Area of standing water under the vapor barrier. Near center most brick column. From the entrance to the crawlspace move to the back of the crawlspace 15ft, facing the rear wall move to the left 5 feet standing water is present there under the vapor barrier.