



Kubota

S Series

SVL65-2HFWC

*** EQUIPMENT IN STANDARD MACHINE ***

FEATURES

Vertical Lift Path Loader Frame
 Standard Front Quick Coupler
 Float Standard
 Hydraulic Quick Coupler Option
 Loader Arm Self-Leveling with on/off switch
 Loader Boom Lock
 Open ROPS & Air Conditioned ROPS/FOPS Cab Models
 Adjustable, Vinyl, Suspension Seat
 2" Retractable Seat Belt and 2-Piece Seat Bar
 12V Electric Outlet
 17.4 gpm Auxiliary Hydraulics standard, 27 gpm Option
 Direct To Tank Return Line
 Rigid Mounted Undercarriage, 4 Lower Track Rollers
 Rubber Tracks, 12.6" Standard 15" Optional
 Two Speed Travel System
 Automatic Wet Disk Parking Brake
 Kubota 4 Hydraulic Pump Load Sensing System
 2 Gear, 2 Variable Displacement Pumps
 Hydraulic Joystick Controls, Optional Multi-Function Grips
 ISO Operating Pattern
 Hand And Foot Throttle Controls
 Electronic Travel Torque Management
 Automatic Glow Plugs
 Key Switch Stop System
 Self Bleed Fuel System
 2 Front and 2 Rear Working Lights
 Hour Meter, Engine Temperature and Fuel Gauges and Warning Lights
 Horn and Backup Alarm
 Lockable Fuel Cap
 Bolt On Grab Handles to enter machine

BASIC UNITS

SVL65-2HFWC, 15.0" Rubber Tracks, A/C ROPS/FOPS Cab
 Hydraulic Quick Coupler, High Flow Hydraulics & MF Grips
 ENGINE
 V2607-CE-TE4 Tier 4 Final Diesel Engine
 4 Cylinder, 4 Cycle, Turbo Charged 68 Gross HP @ 2400 rpm (SAE J1995)

DIMENSIONS

Cab Height 79.9"
 Width (without attachment) 65.2"
 Width with wide track option (without attachment) 67.7"
 Length (without attachment) 107.6"
 Length of Track on Ground 57.9"

OPERATIONAL

DIMENSIONS
 Operating Weight: SVL65-2, 12.6" Rubber Tracks, Open ROPS/FOPS Cab, Mechanical Quick Coupler 8,105 lbs.
 Rated Operating Capacity (@ 35% of Tipping Load) 2,100 lbs.
 Rated Operating Capacity (ROC) @ 50% of Tipping Load 3,000 lbs.
 Tipping Load 6,000 lbs.
 Auxiliary Hydraulics Flow 17.4 gpm
 Travel Speed (Low / High) 4.9 / 7.1 mph
 Reach @ Maximum Height 34.9"
 Height to Hinge Pin 118.5"
 Ground Pressure (Standard Track) 5.0 psi.
 Ground Pressure (Wide Track) 4.2 psi

* includes operator's weight, 165 lbs.

SVL65-2HFWC Base Price: \$76,525.00

Selected Kubota Attachments

(1) 68" Heavy Duty, Low Profile, Long Floor, Cutting Edge, Side Cutter, 17.9 cu-ft heaped capacity
 AP-HD68LLC-68" Heavy Duty, Low Profile, Long Floor, Cutting Edge, Side Cutter, 17.9 cu-ft heaped capacity

(1) STROBE LIGHT KIT
 S6676-STROBE LIGHT KIT

Selected Land Pride Attachments

(1) 30 Series Pallet Fork, 48" Width3,000 lb. Capacity
 PFL3048-99-30 Series Pallet Fork, 48" Width3,000 lb. Capacity

Total Kubota Attachments: \$2,608.00

Total Land Pride Attachments: \$1,662.00

Total Attachments: \$4,270.00

Configured Price: \$80,795.00

Sourcewell Discounts:

Kubota Items: (\$18,991.92)

Land Pride Items: (\$415.50)

Total Discount: (\$19,407.42)

SUBTOTAL: \$61,387.58

Kubota Item Fees:

Dealer Assembly: \$36.67

Freight Cost: \$831.25

PDI: \$400.00

Land Pride Item Fees:

Dealer Assembly: \$75.00

Delivery Fee: \$120.00

Freight: \$662.50

REARVIEW CAMERA KIT - 77700-07933 \$865.00

Total Unit Price: \$64,378.00

Quantity Ordered: 1

Final Sales Price: \$64,378.00

Purchase Order Must Reflect Final Sales Price.

To order, place your Purchase Order directly with the quoting dealer

*All equipment specifications are as complete as possible as of the date on the quote. Additional attachments, options, or accessories may be added (or deleted) at the discounted price. All specifications and prices are subject to change. Taxes are not included. The PDI fees and freight for attachments and accessories quoted may have additional charges added by the delivering dealer. These charges will be billed separately. Prices for product quoted are good for 60 days from the date shown on the quote. All equipment as quoted is subject to availability.